

## OMNITRONIC MAXX-1206DSP 2.1 Active System white

Art. No.: 11039063

GTIN: 4026397729504



**List price: 712.81 €**

incl. 19% VAT.

### Features:

- For application areas such as: Mobile use; Trade fair and shop fitting; installation; home entertainment; restaurants, bars and hotels; product presentations and lectures; mobile djs / entertainer
- <p>OMNITRONIC MAXX-1206 2-way Top 6.5" 2x white  
**6.5" passive full-range speaker, 100 W RMS**
- 2-way bass-reflex system with 6.5" bass-midrange speaker and 1" titanium compression driver
- Serve as a mobile 2.1 system together with the MAXX-1206 subwoofer
- With passive 2-way crossover, PTC tweeter protection
- With rigging points
- White metal grille with acoustic foam
- Rugged carrying handle
- 2 pieces per set
- Application possibility: Standing; suspended; monitoring; on stand
- <p>OMNITRONIC MAXX-1206DSP 2.1 Active Subwoofer 12" white  
**High-power 12" active subwoofer with DSP and Bluetooth, 450 watts**
- 12" subwoofer with Class D amplifier in bassreflex cabinet
- Amplifier power: 250 W RMS + 2 x 100 W RMS for two satellites
- Serves as a mobile 2.1 system together with MAXX-1206 2-way tops
- Balanced signal input XLR/6.3 mm jack L/R
- Additional stereo RCA input, with level switch
- Separate volume control for subwoofer and satellites
- Stereo/mono selection
- Digital signal processor
- DSP presets: FLAT; DJ; LIVE
- Control via Bluetooth
- White metal grille with acoustic foam

### Logistic

EAN / GTIN: 4026397729504

Weight: 37,40 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

- Rubber feet
- Wheels optional
- Application possibility: Standing

## Technical specifications:

|         |          |
|---------|----------|
| Weight: | 34.35 kg |
|---------|----------|

### OMNITRONIC MAXX-1206 2-way Top 6.5" 2x white

|                    |                                                                                                                |
|--------------------|----------------------------------------------------------------------------------------------------------------|
| Power:             | Program: 200W<br>Rated: 100W RMS                                                                               |
| Frequency range:   | 100 - 17000 Hz                                                                                                 |
| Sensitivity:       | 91 dB                                                                                                          |
| Max. SPL:          | 115 dB                                                                                                         |
| Dispersion angle:  | 90° x 60°                                                                                                      |
| Impedance:         | 4 ohms                                                                                                         |
| Attachment system: | Flange: Ø 35mm                                                                                                 |
| Flying points:     | 3 x M8 thread                                                                                                  |
| Connections:       | Input: speaker via 1 x speaker built-in socket (F)                                                             |
| Speaker:           | 1 x woofer 6.5"<br>Basket material: steel<br>Conematerial: cardboard/paper<br>1 x compression tweeter highs 1" |
| Type of speaker:   | Compact cabinet speaker                                                                                        |
| Carrying handle:   | 1 pc/pcs                                                                                                       |
| Material:          | MDF (medium density fiberboard), 16 mm                                                                         |
| Color:             | White, textured coating, painted                                                                               |
| Dimensions:        | Width: 20.4 cm<br>Depth: 19 cm<br>Height: 36.2 cm                                                              |
| Weight:            | 12.70 kg                                                                                                       |

### OMNITRONIC MAXX-1206DSP 2.1 Active Subwoofer 12" 2x white

|                    |                                                                                                      |
|--------------------|------------------------------------------------------------------------------------------------------|
| Power supply:      | 230 V AC, 50 Hz                                                                                      |
| Power consumption: | 500 W                                                                                                |
| Protection class:  | Protection class I                                                                                   |
| Power connection:  | Mains input via IEC connector (M) mounting<br>version power supply cord with safety plug<br>included |
| Fuse:              | 5 x 20 mm, T 4 A fuse replaceable                                                                    |
| Power:             | Rated: 250W RMS LF<br>Rated: 2x 100W RMS HF                                                          |
| Frequency range:   | 38 - 250 Hz bass<br>100 - 17000 Hz top                                                               |

|                        |                                                                                                                                                                                                                                     |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sensitivity:           | 97 dB                                                                                                                                                                                                                               |
| Max. SPL:              | 119 dB                                                                                                                                                                                                                              |
| DSP:                   | Digital signal processor                                                                                                                                                                                                            |
| DSP presets:           | FLAT; DJ; LIVE                                                                                                                                                                                                                      |
| Control:               | Bluetooth                                                                                                                                                                                                                           |
| Bluetooth device name: | OMNITRONIC MAXX1206                                                                                                                                                                                                                 |
| Attachment system:     | Flange: M20 thread                                                                                                                                                                                                                  |
| Circuitry:             | Class D                                                                                                                                                                                                                             |
| Control elements:      | Power switch, level control, Input sensitivity switch, connect, tone control                                                                                                                                                        |
| Controls:              | Limiter                                                                                                                                                                                                                             |
| Status LED:            | Power, signal, limit, pairing, DSP presets                                                                                                                                                                                          |
| Connections:           | Input: line via 1 x stereo RCA<br>Input: line via 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version)<br>Output: line via 2 x 3-pin XLR (M) mounting version<br>Output: speaker via 2 x speaker built-in socket (F) |
| Input channels:        | 1 x stereo via XLR or RCA or bluetooth, channel control via rotary dial                                                                                                                                                             |
| Speaker:               | 1 x woofer 12" with ferrit magnet<br>Basket material: steel<br>Conematerial: cardboard/paper                                                                                                                                        |
| USB port:              | 1 x type C, 2 A                                                                                                                                                                                                                     |
| Type of speaker:       | Subwoofer                                                                                                                                                                                                                           |
| Type of construction:  | Vented                                                                                                                                                                                                                              |
| Transport aid:         | Rubber feet<br>Wheels optional                                                                                                                                                                                                      |
| Material:              | MDF (medium density fiberboard), 16 mm                                                                                                                                                                                              |
| Color:                 | White, textured coating, painted                                                                                                                                                                                                    |
| Dimensions:            | Width: 38.4 cm<br>Depth: 47.4 cm<br>Height: 45.8 cm                                                                                                                                                                                 |
| Weight:                | 19.50 kg                                                                                                                                                                                                                            |

## Scope of delivery:

### 1 x OMNITRONIC MAXX-1206 2-way Top 6.5" & 2x white

2 x top  
2 x speaker cable

### 1 x OMNITRONIC MAXX-1206DSP 2.1 Active Subwoofer 12" & white

1 x bass  
1 x power cord  
1 x strap  
1 x user manual  
1 x declaration of conformity