

OMNITRONIC MAXX-1508NG 2.1 Active System

Mobile 2.1 system with DSP, mixer, stereo Bluetooth link, 800 W RMS

Art. No.: 11039070

GTIN: 4026397753714



List price: 1010.31 €

incl. 19% VAT.

Features:

- Multiband Compressor; Multistep Limiter; Active Phase Correction; Delay Compensation; 3-band EQ
- 4-channel mixer
- Stereo Bluetooth link for wireless stereo operation with 2 systems linked together
- Black metal grille with acoustic foam
- 2 Rugged carrying handles
- Wheels optional
- 4 x rubber feet
- **integrated amplifier module**
- Digital signal processor
- DSP presets: MUSIC; LIVE; SPEECH; 80 Hz low cut; FLAT
- Control via Bluetooth
- Bluetooth: operating range up to 10m in buildings
- Multicolor LCD display
- The device is cooled by low-noise cooling fan
- <p>OMNITRONIC MAXX-1508NG 2-way Top 8"
- **8" passive full-range speaker, 150 W RMS**
- Black metal grille with acoustic foam
- Rugged carrying handle
- 4 x rubber feet

Logistic

EAN / GTIN: 4026397753714

Weight: 51,18 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

Technical specifications:

Output power:	800 W RMS system
Frequency range:	40 - 20000 Hz system
Max. SPL:	132 dB system
Weight:	45.05 kg

OMNITRONIC MAXX-1508NG Active Subwoofer 15"

Frequency range:	40 - 150 Hz bass
Max. SPL:	129 dB
DSP:	Multiband Compressor; Multistep Limiter; Active Phase Correction; Delay Compensation; 3-band EQ
Attachment system:	M20 thread
Speaker:	1 x woofer 15" with ferrit magnet Basket material: steel Voice coil lows 3" Conematerial: cardboard/paper
Type of speaker:	Subwoofer
Type of construction:	Vented
Carrying handle:	2 pc/pcs
Transport aid:	Wheels optional 4 x rubber feet
Material:	MDF (medium density fiberboard), 15 mm
Color:	Black, textured coating, painted
Dimensions:	Width: 43.5 cm Depth: 52 cm Height: 51 cm
Power supply:	230 V AC, 50 Hz
Power consumption:	400 W
Protection class:	Protection class I
Output power:	1 x 500 W RMS LF 2 x 150 W RMS (8 ohms) HF 1 x 300 W RMS (4 ohms) HF
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug included
Fuse:	5 x 20 mm, T 3.15 A fuse replaceable
DSP:	Digital signal processor
DSP presets:	MUSIC; LIVE; SPEECH; 80 Hz low cut; FLAT
Cooling:	1 x low-noise cooling fan
Filter:	Low cut: 80 Hz
Control:	Bluetooth
Bluetooth device name:	MAXX-1508NG
Range:	Bluetooth: range up to 10m in buildings
Carrier frequency:	2.4 GHz
Circuitry:	Class D
Display type:	Multicolor LCD display

Control elements:	Power switch, encoder, menu, BACK button
Controls:	Overheat; short-circuit; DC voltage; limiter
Status LED:	Limit
Connections:	Input: mic/line via 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Input: line via 2 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version) Input: line via 1 x RCA (F) mounting version Output: line via 2 x 3-pin XLR (M) mounting version Output: speaker via 2 x speaker built-in socket (F)
Input channels:	1 x stereo via RCA, channel control via rotary dial 3 x mono via XLR or jack, channel control via rotary dial
Crossover frequency:	100 Hz
Cable construction:	3 x 0.75 mm² H05VV-F
Cable length:	1.8 m
Weight:	0.13 kg

OMNITRONIC MAXX-1508NG 2-way Top 8"

Power:	Program: 300W Rated: 150W RMS
Frequency range:	90 - 20000 Hz
Sensitivity:	93 dB (1W/1m)
Max. SPL:	118 dB
Dispersion angle:	90° x 70°
Impedance:	8 ohms
Attachment system:	Flange: Ø 35mm
Connections:	Speaker via 1 x speaker built-in socket (F)
Crossover frequency:	2800 Hz
Speaker:	1 x woofer 8" with ferrit magnet Basket material: steel Conematerial: cardboard/paper Voice coil lows 1,5" 1 x compression tweeter highs 1" Voice coil compression tweeter highs 1"
Type of speaker:	Compact cabinet speaker
Type of construction:	Vented
Carrying handle:	1 pc/pcs
Transport aid:	4 x rubber feet
Material:	MDF (medium density fiberboard), 15 mm, painted
Color:	Black, textured coating, painted
Dimensions:	Width: 27 cm Depth: 27 cm Height: 44.2 cm
Weight:	9.90 kg
Weight:	9.1 kg

Cable construction:	1 x speaker cable
Cable length:	5 m

Scope of delivery:

1 x OMNITRONIC MAXX-1508NG Active Subwoofer 15"

- 1 x bass
- 1 x power cord
- 1 x user manual
- 1 x declaration of conformity

2 x OMNITRONIC MAXX-1508NG 2-way Top 8"

- 1 x top
- 1 x speaker cable