

## OMNITRONIC PAS-152PRO Subwoofer

15" bassreflex subwoofer with 1000 W RMS, 4 ohms

Art. No.: 11039622

GTIN: 4026397479348



**The article is no longer in our assortment.**

### Features:

- Pro bassreflex subwoofer of a very high efficiency
- Housing made of 18 mm plywood multilayered glued
- 2 x 38 cm (15") bass speaker with diecast aluminum basket
- Parallel Speaker connectors
- M20 metal flange for PAS top speakers
- Carrying handles and rubber feet
- Matching castors optionally available
- Scratch-resistant lacquer surface
- Impact-resistant steel grille with acoustic foam
- Ideal as PA system or amplification system for medium-sized and large discotheques
- Wheels optional

### Logistic

EAN / GTIN: 4026397479348

Weight: 63,00 kg

Length: 1.05 m

Width: 0.70 m

Height: 0.59 m

Bulky product

### Technical specifications:

|                  |                                                    |
|------------------|----------------------------------------------------|
| Power:           | Program: 2000W<br>Rated: 1000W RMS                 |
| Frequency range: | 40 - 200 Hz                                        |
| Sensitivity:     | 101 dB (1W/1m)                                     |
| Impedance:       | 4 ohms                                             |
| Connections:     | Input: speaker via 2 x speaker built-in socket (F) |
| Speaker:         | 2 x woofer 15"                                     |
| Type of speaker: | Subwoofer                                          |

|                       |                                                   |
|-----------------------|---------------------------------------------------|
| Type of construction: | Vented                                            |
| Transport aid:        | Wheels optional                                   |
| Dimensions:           | Width: 61 cm<br>Depth: 95.7 cm<br>Height: 48.2 cm |
| Weight:               | 56.95 kg                                          |
| Components:           | 2 x 38 cm woofer (2 x 15")                        |
| Connection:           | 2 Speaker sockets                                 |
| Sensitivity:          | 101 dB                                            |
| Maximum SPL:          | 133 dB                                            |

**Scope of delivery:**