

**PSSO CSA-228W top, white**

Compact speaker array for touring purposes and permanent installations

**Art. No.: 11040801**

GTIN: 4026397362831

**The article is no longer in our assortment.****Description:**

The CSA high-mid speaker units, they are very powerful and feature a horn tweeter with 3.5 cm driver and, depending on the model, one or two 20 cm woofers (CSA-218 or CSA-228 respectively). The tweeter of the smaller version, the CSA-218, ensures a horizontal and vertical dispersion angle of 90°. Thus the CSA-218 can be used standing or lying without having to make compromises in terms of sound or directivity. The larger version, the CSA-228, is designed for upright use and has a dispersion angle of 90° x 40°.

Where should the CSA be used?

We can recommend mobile use. Concerts or weddings are supported in a powerful, resonant and linear way. But as it is quite versatile, the CSA should not be reduced to our suggestion only.

**Features:**

- Compact speaker array for permanent installations and touring purposes
- Horn tweeter for powerful highs
- Lightweight housing due to high-quality plastic
- Wide horizontal dispersion angle

**Technical specifications:**

Frequency range: 75 - 18000 Hz

Dimensions: Width: 66.5 cm

**Logistic**

EAN / GTIN: 4026397362831

Weight: 16,75 kg

Length: 0.75 m

Width: 0.42 m

Height: 0.38 m

|                         |                                                  |
|-------------------------|--------------------------------------------------|
|                         | Depth: 34 cm<br>Height: 25 cm                    |
| Weight:                 | 14.50 kg                                         |
| Rated power:            | 300 W RMS                                        |
| Program power:          | 600 W                                            |
| Components:             | 2 x 20 cm woofer (2 x 8"), 3.4 cm driver (1.33") |
| Connection:             | 2 Speaker sockets (4-pin)                        |
| Sensitivity:            | 95 dB                                            |
| Maximum SPL:            | 119 dB                                           |
| Impedance:              | 8 ohms                                           |
| Crossover frequency:    | 2.5 kHz                                          |
| Dispersion angle:       | H=90°, V=40°                                     |
| Dimensions (H x W x D): | 250 x 665 x 340 mm                               |

### Scope of delivery: