

PSSO CSA-228A top, active, black

Pro active PA speaker system with biamp amplifier, 450 W

Art. No.: 11040815

GTIN: 4026397527643



Features:

- Active full-range top speaker, qualified for suspension
- For permanent installations and touring purposes
- Class D biamp power amplifier (450 W)
- Efficient, light-weight switch mode power supply with energy saving mode
- Light-weight cabinet due to high-quality special plastic (15 kg only)
- Elegant housing design
- 2 x 20 cm (8") bass speaker and 3.5 cm (1.35") titanium compression horn driver
- 90° x 40° nominal coverage
- Balanced XLR input
- Speaker flange for mobile use included in the delivery
- PowerCon mains input
- Applications: as monitor, on a subwoofer or speaker stand, suspended
- Matching mounting brackets and flying hardware available as accessories

Logistic

EAN / GTIN: 4026397527643

Weight: 18,60 kg

Length: 0.76 m

Width: 0.42 m

Height: 0.40 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Frequency range:	70 - 18000 Hz
Speaker:	2 x woofer 8"
Type of speaker:	Compact cabinet speaker
Rated power:	450 W
Components:	HF: 3.5 cm (1.35"), LF: 2 x 20 cm (8")

Crossover frequency:	2.5 kHz
Dispersion angle:	90° x 40°
Maximum SPL:	119 dB
Acoustic loading:	Bassreflex
Cabinet material:	HIPS
Amplifier:	Class D
THD:	<0.05 %
S/N ratio:	>80 dB
Damping factor:	>50
Input sensitivity:	2 V
Input impedance:	40 kohms/20 kohms (bal./unbal.)
Signal input:	XLR
Power consumption:	550 W
Protection circuits:	Limiter, overheat, overload, short-circuit
LED indicators:	Power, clip
Weight:	16 kg

Scope of delivery: