

PSSO K-215SE 2-Way Top 600W

PRO PA speaker, 15" woofer, 1.5" horn, 600 W RMS, 8 ohms

Art. No.: 11041109

GTIN: 4026397545401



Features:

- Rugged full-range top speaker, qualified for suspension and touring applications
- Housing made of 15 mm/18 mm birch plywood
- 38 cm (15") bass speaker with diecast aluminum basket
- Rotatable constant directivity horn tweeter with titanium diaphragm
- Horn exit 38 mm (1.5")
- Voice coil 72 mm (2.8")
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- Passive 2-way crossover
- Bassreflex system
- Parallel Neutrik Speakon connectors
- Trapezoidal multi-functional housing with scratch-resistant lacquer surface
- Impact-resistant steel grille with acoustic foam
- Dual-angle-Flange for stand installation
- Applications: standing, as monitor, on a subwoofer or speaker stand, suspended
- CELTO ACOUSTIQUE driver
- Built with NEUTRIK connector
- European engineering

Logistic

EAN / GTIN: 4026397545401

Weight: 32,45 kg

Length: 0.51 m

Width: 0.49 m

Height: 0.79 m

Bulky product

Technical specifications:

Power:	Program: 1200W Rated: 600W RMS
Frequency range:	47 - 19000 Hz
Sensitivity:	99 dB (1W/1m)

Max. SPL:	127 dB
Dispersion angle:	80° x 50°
Impedance:	8 ohms
Connections:	Input: speaker via 2 x 2-pin SpeakON mounting version (F)
Crossover frequency:	1500 Hz
Speaker:	1 x woofer 15" 1 x horn 1.35"
Type of speaker:	Compact cabinet speaker
Use of brands:	CELTO ACOUSTIQUE driver Built with NEUTRIK connector
Dimensions:	Width: 44.5 cm Depth: 41.5 cm Height: 71 cm
Weight:	29.45 kg

Scope of delivery:

- 1 x top
- 1 x user manual