

PSSO PRIME-315 Club Speaker System

PRO PA speaker, 2 x 15" woofer, 6.5" + 2 x 1.4" horn-loaded, 1800 W RMS (Biamp)

Art. No.: 11041172

GTIN: 4026397516388



Features:

- Rugged pro PA speaker, qualified for suspension and clubs
- Biamp operation
- Housing made of 25 mm (17 layers) and 18 mm (13 layers) birch plywood
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- 2 x 38 cm neodymium bass speaker (15") with diecast aluminum basket
- 16.5 cm neodymium midrange speaker (6.5") with diecast aluminum basket, 51 mm voice coil (2")
- 36 mm neodymium driver (1.4"), 72 mm voice coil (2.8")
- Bassreflex system
- Neutrik Speakon connectors
- Scratch-resistant lacquer surface
- Applications: standing or suspended
- CELTO ACOUSTIQUE driver
- Built with NEUTRIK connector
- European engineering

Logistic

EAN / GTIN: 4026397516388

Weight: 80,00 kg

Length: 0.90 m

Width: 0.60 m

Height: 0.90 m

Bulky product

Technical specifications:

Power:	Program: 300W MHF
	Rated: 300W RMS MHF
	Rated: 1800W RMS LF
	Program: 3600W LF

Frequency range:	46 - 19000 Hz
------------------	---------------

Sensitivity:	102 dB
Max. SPL:	140 dB 8 ohms HF
Dispersion angle:	80° x 50°
Impedance:	4/8 ohms biamp
Connections:	Speaker via 2 x 4-pol SpeakON mounting version (F)
Crossover frequency:	2200 Hz 650 Hz
Speaker:	2 x woofer 15" Voice coil lows 4" 1 x horn 6.5" Voice coil compression tweeter highs 2" 2 x horn vent 1.35" Voice coil compression tweeter highs 3"
Use of brands:	CELTO ACOUSTIQUE driver Built with NEUTRIK connector
Dimensions:	Width: 83.8 cm Depth: 58.4 cm Height: 81.5 cm
Weight:	75 kg

Scope of delivery: