

## CELTO iFIX10 G2 2-way Coaxial Speaker white

Passive speaker with 10" woofer, 1" driver and 600 W

Art. No.: 11043571

GTIN:



**List price: on demand €**

incl. 19% VAT.

### Features:

- Real 300 W power handling with high-end sound quality
- Coaxial transducer for unmatched spatial coherence
- High efficiency for incredible SPL to size ratio
- HF compression driver with ketone polymere dome
- With mounting bracket
- CELTO ACOUSTIQUE driver
- Available in various colors
- For application areas such as: Theater; sports centres/gyms; clubs/dancing school; restaurants, bars and hotels

### Logistic

### Technical specifications:

|                    |                                                 |
|--------------------|-------------------------------------------------|
| Power:             | Peak: 1200W<br>Program: 600W<br>Rated: 300W AES |
| Frequency range:   | 95 - 22000 Hz                                   |
| Sensitivity:       | 97 dB (1W/1m)                                   |
| Max. SPL:          | 128 dB                                          |
| Dispersion angle:  | 80° conical                                     |
| Impedance:         | 8 ohms                                          |
| Attachment system: | Mounting bracket                                |

|                       |                                                                                                                                                                                                   |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Connections:          | Input: speaker via screw plug-in terminal                                                                                                                                                         |
| Crossover frequency:  | Passive 1500 Hz<br>Recommended<br>In subwoofer combination<br>High-pass 90-130 Hz, 24db/oct with iFIX13S or iFIX17S subwoofer                                                                     |
| Speaker:              | 1 x woofer 10" with ferrit magnet<br>Voice coil lows 2.5"<br>Basket material: aluminum<br>1 x annular compression driver 1"<br>Voice coil annular 1.75"<br>Diaphragmmaterial: PEEK (H.T. polymer) |
| Type of speaker:      | On ceiling/on wall speaker; coaxial speaker                                                                                                                                                       |
| Type of construction: | Closed Box                                                                                                                                                                                        |
| Use of brands:        | CELTO ACOUSTIQUE driver                                                                                                                                                                           |
| Material:             | Birch multiplex, 15 mm, CNC made with tongue and grove assembly                                                                                                                                   |
| Color:                | White, textured coating, painted                                                                                                                                                                  |
| Dimensions:           | Width: 30 cm<br>Depth: 30.4 cm<br>Height: 30 cm                                                                                                                                                   |
| Weight:               | 12.85 kg                                                                                                                                                                                          |

**Scope of delivery:**

- 1 x top
- 1 x mounting bracket
- 1 x nut
- 8 x washer
- 1 x safety eyelet
- 2 x screw
- 1 x screw plug-in terminal