

CELTO iFIX13S Vented Subwoofer black

Impressive 13" woofer, compact design

Art. No.: 11043620

GTIN:



Features:

- Long excursion 13" LF drivers with $\pm 8.5\text{mm}$ linear Xmax
- Trimmed chassis for 15" performance in 12" size cabinet
- Incredible deep tones from ultra compact cabinet
- High efficiency for incredible SPL to size ratio
- Six M8 flying points for added versatility
- Heavy braced cabinet for vibration free dynamic response
- Birch multiplex cabinet with tongue and groove assembly
- With rigging points
- Any RAL color available on request
- Available in various colors
- For application areas such as: Theater; sports centres/gyms; clubs/dancing school; restaurants, bars and hotels

Logistic

Technical specifications:

Power:	Program: 1000W Rated: 500W RMS
Frequency range:	42 - 1500 Hz
Sensitivity:	97 dB (1W/1m)
Max. SPL:	130 dB
Dispersion angle:	Omnidirectional
Impedance:	6 ohms

Flying points:	6 x M8 thread
Connections:	Input: speaker via screw terminal
Crossover frequency:	Active mode only Recommended High-pass 35 Hz, 24db/oct Low-pass 120 Hz, 24db/oct
Speaker:	1 x woofer 13.5" with ferrit magnet Voice coil lows 3"
Type of speaker:	Subwoofer
Type of construction:	Vented
Material:	Birch multiplex, 18 mm, CNC made with tongue and grove assembly
Color:	Black, textured coating, painted; any RAL color available on request
Dimensions:	Width: 54.5 cm Depth: 50 cm Height: 42.3 cm
Weight:	25.35 kg

Scope of delivery:

1 x bass