

CELTO CMP10 2-way Coaxial Speaker

Passive speaker with 10" woofer, 1" driver and 600 W

Art. No.: 11043630

GTIN:



Features:

- With rigging points
- CELTO ACOUSTIQUE driver
- Built with NEUTRIK connector
- Rubberized Polyurea coating
- For application areas such as: Concerts/FoH's; clubs/dancing school; wedding/gala/events; Trade fair and shop fitting; installation; mobile use; stage; theater; rental; product presentations and lectures; trade fair construction

Logistic

Technical specifications:

Power:	Peak: 1200W
	Program: 600W
	Rated: 300W AES
Frequency range:	78 - 22000 Hz
Sensitivity:	97 dB (1W/1m)
Max. SPL:	128 dB
Dispersion angle:	80° conical
Impedance:	8 ohms
Flying points:	7 x M8 thread
Control elements:	Mode switch (1+1- / 2+2-)

Connections:	2 x 4-pol SpeakON mounting version (F)
Crossover frequency:	1500 Hz
Speaker:	1 x woofer 10" with ferrit magnet Basket material: aluminum Voice coil lows 2.5" 1 x annular compression driver 1" with neodymium magnet Voice coil annular 1.75" Diaphragmmaterial: PEEK (H.T. polymer)
Type of speaker:	Coaxial speaker; compact cabinet speaker
Type of construction:	Vented
Use of brands:	CELTO ACOUSTIQUE driver Built with NEUTRIK connector
Material:	Birch multiplex
Color:	Black, rubberized Polyurea coating
Dimensions:	Width: 44 cm Depth: 29.8 cm Height: 30.6 cm
Weight:	15.00 kg

Scope of delivery:

1 x top