

## CELTO VCM12 2-way Coaxial Monitor

Compact and low-profile coaxial monitor

Art. No.: 11043671

GTIN: 4026397668216



### Features:

- Real 400 W RMS power capacity
- Natural sound and incredible holographic reproduction
- Optimized for smooth frequency response in and out axis
- Premium Neodymium custom made driver
- Dual monitor angle, for short monitoring
- Touring grade soft-touch black painting
- With QuickFly system
- With rigging points
- High-quality workmanship with birch multiplex 18 mm, black, rubberized Polyurea coating
- CELTO ACOUSTIQUE driver
- Built with NEUTRIK connector
- For application areas such as: Theater; advertisement/Shop window; concerts/FoH's; clubs/dancing school; restaurants, bars and hotels

### Logistic

EAN / GTIN: 4026397668216

Weight: 22,45 kg

Length: 0.53 m

Width: 0.64 m

Height: 0.45 m

### Technical specifications:

|                   |                                  |
|-------------------|----------------------------------|
| Power:            | Program: 800W<br>Rated: 400W RMS |
| Frequency range:  | 69 - 18000 Hz                    |
| Sensitivity:      | 100 dB                           |
| Max. SPL:         | 132 dB                           |
| Dispersion angle: | 70° conical                      |

|                      |                                                                                                                                                                                                                                                      |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Impedance:           | 8 ohms                                                                                                                                                                                                                                               |
| Attachment system:   | Flange: Ø 35mm variable tilt<br>QuickFly system                                                                                                                                                                                                      |
| Flying points:       | 14 x M8 thread                                                                                                                                                                                                                                       |
| Connections:         | Speaker via 2 x 4-pol SpeakON mounting version (F)                                                                                                                                                                                                   |
| Crossover frequency: | 1400 Hz<br>Recommended<br>Low-pass 150 Hz, 24db/oct in full-range mode<br>Low-pass 60-120 Hz with subwoofer                                                                                                                                          |
| Speaker:             | 1 x woofer 12" with neodymium magnet<br>Basket material: aluminum<br>Voice coil woofer in/out wound 3"<br>1 x compression tweeter highs 1,5" with neodymium magnet<br>Voice coil compression tweeter highs 2.8"<br>Diaphragmmaterial: Aquaplased TC4 |
| Type of speaker:     | Stage monitor; coaxial speaker; compact cabinet speaker                                                                                                                                                                                              |
| Use of brands:       | CELTO ACOUSTIQUE driver<br>Built with NEUTRIK connector                                                                                                                                                                                              |
| Material:            | Birch multiplex, 18 mm, CNC made with tongue and grove assembly                                                                                                                                                                                      |
| Color:               | Black, rubberized Polyurea coating                                                                                                                                                                                                                   |
| Dimensions:          | Width: 50.4 cm<br>Depth: 42.7 cm<br>Height: 33 cm                                                                                                                                                                                                    |
| Weight:              | 18.05 kg                                                                                                                                                                                                                                             |

### Scope of delivery:

1 x compact cabinet speaker