CELTO CSW221 Subwoofer

21" bassreflex subwoofer with 3600 W AES

Art. No.: 11043697

GTIN: 4026397668100

Features:

- Clean and deep reproduction
- Premium custom made driver
- Heavy braced cabinet for vibration free dynamic response
- CELTO ACOUSTIQUE driver
- Built with NEUTRIK connector
- For application areas such as: Concerts/FoH's; clubs/dancing school; wedding/gala/events; installation; stage; multi-purpose hall

Logistic

EAN / GTIN: 4026397668100

Technical specifications:

Power:	Peak: 14400W Rated: 3600W AES Program: 7200W
Frequency range:	28 - 1000 Hz
Sensitivity:	102 dB (1W/1m)
Max. SPL:	143 dB
Dispersion angle:	Omnidirectional
Impedance:	4 ohms
Attachment system:	Flange: 2x M20 thread
Connections:	2 x 4-pol SpeakON mounting version (F)

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Crossover frequency:	Active mode only Recommended Low-pass 90 Hz, 24db/oct
Speaker:	Woofer 21" with ferrit magnet Basket material: aluminum Voice coil woofer in/out wound 4.5"
Type of speaker:	Subwoofer
Type of construction:	Vented
Use of brands:	CELTO ACOUSTIQUE driver Built with NEUTRIK connector
Material:	Birch multiplex
Color:	Black, textured coating, painted
Dimensions:	Width: 122.6 cm Depth: 80.5 cm Height: 58.8 cm
Weight:	98.50 kg

Scope of delivery:

1 x bass

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.