

INTUSONIC 6FP100T 6.5" 2-way Fullrange Speaker white

6.5" installation speaker 80W AES, 8 ohms, 116.5 dB max. SPL

Art. No.: 12604004

GTIN: 5060502923042



Description:

The INTUCAB 6FP100T is the most universal choice for audio systems requiring a small footprint, without sacrifice to sound quality and SPL. The multitude of connections (Speakon-compatible and 5mm terminal strip), as well as the available input transformer option for 100V systems, contribute further to its versatility. Mounting options include VESA, M6 and M10 mounting points, plus the (patent-pending) L-shaped reversible rear panel allowing for suspended mounting, truss mounting and bracket mounting. Available in black and white structural paint finish. Add the INTUCAB 8SM300T Subwoofer for extended low frequency performance.

Logistic

EAN / GTIN: 5060502923042  
Weight: 8,85 kg  
Length: 0.37 m  
Width: 0.32 m  
Heigth: 0.30 m

Features:

- Reversible rear panel with 3 mounting options
- 1" HF compression driver & wide-dispersion HF horn
- Advanced passive crossover for best sound quality
- 100V transformer kit option (UTK20 - sold separately)
- Horn 90 degree rotatable for horizontal or vertical use
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

|                  |                                 |
|------------------|---------------------------------|
| Power:           | Rated: 80W AES<br>Program: 150W |
| Frequency range: | 75 - 16500 Hz                   |
| Sensitivity:     | 92 dB (1W/1m)                   |

|                       |                                                               |
|-----------------------|---------------------------------------------------------------|
| Max. SPL:             | 116.5 dB                                                      |
| Dispersion angle:     | 90° x 60° rotatable horn                                      |
| Impedance:            | 8 ohms                                                        |
| Attachment system:    | M10 thread<br>3x M6 thread<br>VESA standard                   |
| Connections:          | 2 x speaker built-in socket (F)<br>1 x screw plug-in terminal |
| Speaker:              | 1 x woofer 6.5"<br>1 x compression tweeter highs 1"           |
| Type of speaker:      | Compact cabinet speaker                                       |
| Type of construction: | Vented                                                        |
| Material:             | MDF (medium density fiberboard), 12 mm                        |
| Color:                | White, textured coating, painted                              |
| VESA interface min:   | 7.5 cm x 7.5 cm                                               |
| VESA interface max.:  | 10 cm x 10 cm                                                 |
| Dimensions:           | Width: 22.5 cm<br>Depth: 25.2 cm<br>Height: 32.5 cm           |
| Weight:               | 8.20 kg                                                       |

**Scope of delivery:**

- 1 x top
- 1 x user manual
- 1 x screw plug-in terminal
- 3 x safety eyelet