INTUSONIC PAA71+ Microphone Line Mixer

Microphone line mixer, 7 channels

Art. No.: 12604190

GTIN: 5060502923615

Description:

The INTUWORX PAA71+ is a 7-channel mic/line mixer with an improved design. As the perfect center of any installed sound system, it offers 5 multi-purpose inputs which can either be fed with a balanced microphone signal or an unbalanced stereo line signal. One further balanced stereo line level input is specifically useful for sources at larger distance; the same input can be switched to receive its input signal from the 3.5mm TRS jack on the front, or the built-in LINKOUSTIC 5.2 wireless audio link. An additional dedicated microphone input with adjustable talkover (priority) provides control over announcements. Every input -- with the exception of the balanced stereo input -- is equipped with rear-panel gain control and a front-panel 2-band equalizer. The external shutdown and emergency signal input connections allow integration with central announcement and evacuation systems where required. The adjustable monitor output can either feed a stereo headphone or a balanced mono output.

Features:

- 5 stereo inputs mic/line, switchable
- 1 stereo input AUX/Wireless Audio Link, switchable
- 1 additional microphone input on rear-side with adjustable talkover function
- Adjustable monitor output
- External shutdown and emergency signal connections
- Each microphone input with optional 12 V phantom power
- Control via LINKOUSTIC 4.2 Wireless Audio Link
- (19") 48.3 cm rack installation
- For further information about this product, please refer to the Data Sheet under "Downloads"

Logistic

EAN / GTIN: 5060502923615

Weight: 3,25 kg

Length: 0.54 m

Width: 0.33 m

Heigth: 0.10 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Technical specifications:

Power supply:	115/230 V AC, 50/60 Hz
Power consumption:	Max. 12 W
Protection class:	Protection class I
Power connection:	Mains input via IEC (M) power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, T 0.5 A fuse replaceable
Frequency range:	20 - 20000 Hz
S/N ratio:	>82 dB line
THD:	<0.05 % at 1 kHz
Phantom power:	12 V DC
Control:	LINKOUSTIC 4.2 Wireless Audio Link
Bluetooth device name:	LINKOUSTIC
Carrier frequency:	2.4 GHz
Housing color:	Black
Control elements:	Power switch, source selector, level control per channel, Master control, stereo/mono switch; regular talkover
Status LED:	Power, pairing, level meter
Connections:	Input: line via 2 x 6.3-mm-jack (bal.) Input: AUX via 1 x 3.5 mm jack (stereo) mounting version Input: line via 5 x stereo RCA Input: microphone via 6 x screw plug-in terminal Input: Emergency via 1 x screw plug-in terminal Input: mute function via 1 x screw plug-in terminal Output: master via 2 x screw plug-in terminal Output: rec. via 1 x stereo RCA Output: headphones via 1 x 3.5 mm jack (stereo) mounting version Output: zones via 1 x screw plug-in terminal
Channels:	Input channel: 1 x stereo with Line-Line-Bluetooth switch, channel control via rotary dial, source selector Input channel: 5 x mono + stereo with mic-line switch via RCA or screw plug-in terminal, channel control via rotary dial, 2-band tone control EQ, gain control Input channel: 1 x mono via screw plug-in terminal, channel control via rotary dial, 2-band tone control EQ, gain control, regular talkover Master output: 1 x mono + stereo via screw plug-in terminal, channel control via rotary dial Rec. output: 1 x stereo via RCA Headphones output: 1 x mono + stereo via jack or screw plug-in terminal, channel control via rotary dial
Housing design:	(19") 48.3 cm rack installation
Dimensions:	Width: 48.3 cm Depth: 19 cm Height: 4.4 cm

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Weight:	2.70 kg

Scope of delivery:

1 x mixer
1 x power cord
11 x screw plug-in terminal
1 x plug (male)
4 x foot
1 x antenna
1 x user manual

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.