

## RELACART UT-222 Bodypack with HM-600S Headset

Bodypack transmitter with PLL multifrequency transmitter, 823-832 + 863-865 MHz

Art. No.: 13055231

GTIN: 4026397700510



**List price: 153.51 €**

incl. 19% VAT.

### Features:

- Durable aluminum alloy housing, applicable for touring
  - Pilot frequency squelch technology delete wireless RF interference
  - 10 groups with 90 fixed frequencies within 11 MHz switching bandwidth
  - Easy and error-free synchronization between receiver and transmitter via infrared signal
  - Adjustable input gain
  - RF output power Hi/Low adjustable
  - Lock function for prevents undesired changes to settings
  - Up to 9 transmitters can be operated in parallel without interference
- transmitter**
- Powered by a battery/battery pack
  - Operating range up to 80m
  - UHF 823 - 832 MHz License-free and approved in large parts of Europe
  - UHF 863 - 865 MHz License-free and approved in Europe
- microphone**
- Polar pattern: Omnidirectional
  - For further information about this product, please refer to the Data Sheet under "Downloads"

### Logistic

EAN / GTIN: 4026397700510

Weight: 0,35 kg

Length: 0.29 m

Width: 0.12 m

Heigh: 0.07 m

### Technical specifications:

|                |                          |
|----------------|--------------------------|
| Parallel mode: | Max. 9 transmitter       |
| Weight:        | 0.21 kg                  |
| Type:          | Bodypack with microphone |

|                      |                                                                                        |
|----------------------|----------------------------------------------------------------------------------------|
| Power supply:        | 3V DC                                                                                  |
| Power connection:    | Battery/battery pack                                                                   |
| Battery:             | 2 x Mignon (AA) (not included)                                                         |
| Gain:                | 0 dB<br>-6 dB<br>-12 dB                                                                |
| Range:               | Range up to 80m                                                                        |
| Frequency band:      | UHF 823 - 832 MHz; UHF 863 - 865 MHz                                                   |
| Switching bandwidth: | 11 MHz                                                                                 |
| RF power output:     | UHF 823 - 832 MHz: 10 mW (LO); 40 mW (HI);<br>UHF 863 - 865 MHz: 5 mW (LO); 10 mW (HI) |
| Modulation:          | FM                                                                                     |
| Frequency selection: | 90 switchable frequencies<br>In 10 groups with up to 10 preset frequencies each        |
| Display type:        | OLED display                                                                           |
| Control elements:    | Transmitter power switch (high-low)                                                    |
| Connections:         | Output: Mini XLR (M) 4-pin mounting version                                            |
| Switch:              | On/off/mute switch                                                                     |
| Material:            | Aluminum                                                                               |
| Color:               | Black                                                                                  |
| Dimensions:          | Width: 6.6 cm<br>Depth: 2.3 cm<br>Height: 8.4 cm                                       |
| Weight:              | 0.174 kg                                                                               |
| Type:                | Headset microphone                                                                     |
| Power supply:        | 2-10V DC                                                                               |
| Cable length:        | 1.2 m                                                                                  |
| Capsule type:        | Condenser<br>Size: Ø 5 mm x 6 mm                                                       |
| Polar pattern:       | Omnidirectional                                                                        |
| Frequency range:     | 50 - 18000 Hz                                                                          |
| Sensitivity:         | -47 dB                                                                                 |
| Impedance:           | 1800 Ohm                                                                               |
| Connector type:      | Mini XLR (F) 4-pin                                                                     |
| Color:               | Skin-colored                                                                           |
| Weight:              | 0.028 kg                                                                               |

## Scope of delivery:

1 x transmitter  
 1 x microphone  
 1 x windshield  
 1 x user manual  
 1 x declaration of conformity