

## OMNITRONIC SR-315 Wireless receiver

Multifrequency wireless receiver

Art. No.: 13061500

GTIN: 4026397114027



**The article is no longer in our assortment.**

### Features:

- 16 UHF frequencies (800.100 - 813.000 MHz) selectable via DIP switches
- Telescope antenna
- LED display for power supply and signal input
- Squelch control to eliminate noise bursts
- Output level control
- 6.3 mm and XLR output
- Operation via supplied power unit
- A wireless microphone or a belt transmitter with lavalier microphone or headset microphone can be ordered separately
- License-free and approved in Germany

### Logistic

EAN / GTIN: 4026397114027

Weight: 1,40 kg

Length: 0.35 m

Width: 0.31 m

Height: 0.07 m

### Technical specifications:

|                    |                                                  |
|--------------------|--------------------------------------------------|
| Power consumption: | 130.00 W                                         |
| Frequency band:    | UHF                                              |
| Dimensions:        | Width: 21 cm<br>Depth: 16.5 cm<br>Height: 4.4 cm |
| System:            | Non-diversity, one channel                       |
| Carrier frequency: | UHF 800.100-813.000 MHz (16 ch.)                 |

800.875, 801.375, 802.375, 803.125, 803.875,  
804.500, 805.125, 805.875, 806.625, 807.375,  
807.875, 808.375, 809.125, 810.250, 810.875,  
811.875 MHz

|                      |                                         |
|----------------------|-----------------------------------------|
| Frequency stability: | ±0.005 %                                |
| T.H.D.:              | <1 % at 1 kHz                           |
| Tone signal:         | 32.768 kHz                              |
| S/N-ratio:           | >94 dB at 48 kHz deviation              |
| Input sensitivity:   | 8 dB                                    |
| Selectivity:         | >50 dB                                  |
| Dynamic range:       | >96 dB                                  |
| Modulation method:   | FM-frequency modulation                 |
| Coverage:            | >30 m (with line-of-sight)              |
| Frequency range:     | 50-15000 Hz (±3 dB)                     |
| Audio output:        | Mono 6.3 mm jack socket or balanced XLR |
| Dimensions (LxIxH):  | 210 x 165 x 44 mm                       |
| Weight:              | 0.5 kg                                  |

**Scope of delivery:**