

OMNITRONIC UHF-604 4-channel Wireless Mic System 823-832/863-865 MHz Art. No.: 13063604

True diversity wireless system with auto scan, 7-band EQ and TFT color displays GTIN: 4026397738711



List price: 355.81 €
incl. 19% VAT.

Features:

- Multifrequency wireless receiver with high-quality true diversity reception
 - Ideal for large multi-channel systems
 - Operating range up to 60m with line-of-sight
 - UHF 823 - 832 MHz License-free and approved in large parts of Europe
 - UHF 863 - 865 MHz License-free and approved in Europe
 - Up to 24 transmitters in 2 bands can be operated in parallel without interference
- receiver**
- Automatic frequency setup
 - ID transmitter verification prevents incorrect use and interference from external radio transmitters
 - Different user colors selectable for easy differentiation
 - 7-band equalizer for sound tuning
 - Lock function for prevents undesired changes to settings
 - Multifunctional jogdial for menu settings
 - (19") 48.3 cm rack installation 1 U
 - Ultra-low latency
 - Multicolor TFT display
- microphone**
- Polar pattern: Cardioid
 - Multicolor LCD display
 - Charge status indicator

Logistic

EAN / GTIN: 4026397738711
Weight: 4,00 kg
Length: 0.53 m
Width: 0.29 m
Height: 0.12 m

Technical specifications:

Type:	Wireless set
Range:	Range up to 60m with line-of-sight
Frequency band:	UHF 823 - 832 MHz; UHF 863 - 865 MHz
Switching bandwidth:	11 MHz
Parallel mode:	Max. 24 transmitter in 2 bands
Frequency selection:	Frequencies automatically scannable
Weight:	3.25 kg
Power supply:	100-240 V AC, 50/60 Hz 12V DC 1000 mA
Power consumption:	6.5 W
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter included
Number of channels:	4
Frequency range:	50 - 16000 Hz
S/N ratio:	>80 dB
THD:	<0.5 % at 1 kHz
Diversity:	True diversity
Latency:	< 3 ms
Modulation:	FM
Housing color:	Black
Display type:	5 x multicolor TFT display
Display reading:	Frequency , group , channel , RF signal level; AF audio level , Mute
Control elements:	Level control per channel, power switch, encoder, menu
Connections:	Input: antenna via 2 x BNC (F) Output: microphone via 4 x 3-pin XLR (M) mounting version Output: microphone via 1 x 6.3 mm plug (unbal.)
Equalizer:	Graphic equalizer 7-band
Material:	Metal
Housing design:	(19") 48.3 cm rack installation 1 U
Mounting depth:	21 cm
Dimensions:	Width: 48.5 cm Depth: 21 cm Height: 4.4 cm
Weight:	1.5 kg
Power supply:	3V DC 118 mA
Capsule type:	Dynamic Size: Ø 2.54 mm
Polar pattern:	Cardioid
Battery:	2 x Mignon (AA) (not included)

Sensitivity:	-54 dB
RF power output:	10 mW (HI); 5 mW (LO)
Housing color:	Black
Display type:	Multicolor LCD display
Display reading:	Frequency , charge status indicator , Mute , RF signal level
Switch:	On/off/mute switch
Material:	Metal
Dimensions:	Length: 25.9 cm Diameter: Ø 4.95 cm
Weight:	0.351 kg

Scope of delivery:

- 1 x receiver
- 2 x antenna
- 1 x external mains adapter
- 4 x foot
- 1 x jack cable
- 4 x microphone
- 4 x holder
- 1 x user manual
- 1 x declaration of conformity