



Features:

- Bodypack transmitter with PLL multifrequency transmitter
- Easy and error-free synchronization between receiver and transmitter via infrared signal
- Gain level adjustable in 4 steps
- Powered by a battery/battery pack
- Operating range up to 60m with line-of-sight
- UHF 823 - 832 MHz License-free and approved in large parts of Europe
- UHF 863 - 865 MHz License-free and approved in Europe
- Up to 12 transmitters can be operated in parallel without interference
- Ultra-low latency
- LCD display
- Charge status indicator
- microphone**
- Polar pattern: Cardioid

Logistic

EAN / GTIN: 4026397738759
Weight: 0,15 kg
Length: 0.18 m
Width: 0.13 m
Heigh: 0.04 m

Technical specifications:

Type:	Bodypack with microphone
Power supply:	3V DC 125 mA
Battery:	2 x Mignon (AA) (not included)
Phantom power:	2.4 V DC
Range:	Range up to 60m with line-of-sight
Frequency band:	UHF 823 - 832 MHz; UHF 863 - 865 MHz

Switching bandwidth:	11 MHz
Parallel mode:	Max. 12 transmitter
RF power output:	5 mW (LO); 10 mW (HI)
Latency:	< 3 ms
Modulation:	FM
Housing color:	Black
Display type:	LCD display
Display reading:	Frequency , charge status indicator , Mute , RF signal level; AF audio level , gain
Control elements:	Gain-switch (high-mid-low)
Connections:	Input: microphone via 1 x mini XLR (M) 3-pin mounting version
Switch:	On/off switch; mute control
Material:	Plastic
Color:	Black
Dimensions:	Width: 6.6 cm Depth: 2.8 cm Height: 8.5 cm
Weight:	0.11 kg
Type:	Headset microphone
Power supply:	1.5-10V DC
Cable length:	1.0 m
Capsule type:	Condenser
Polar pattern:	Cardioid
Frequency range:	80 - 18000 Hz
Sensitivity:	-53 dB
Impedance:	600 Ohm
Color:	Skin-colored
Weight:	0.028 kg

Scope of delivery:

1 x transmitter
 1 x microphone
 1 x windshield
 1 x user manual
 1 x declaration of conformity