

## OMNITRONIC UHF-600 Bodypack 520-554 MHz

Bodypack transmitter for UHF-600 receivers

Art. No.: 13063609

GTIN: 4026397738766



**List price: 59.38 €**

incl. 19% VAT.

### Features:

- Bodypack transmitter with PLL multifrequency transmitter
- Easy and error-free synchronization between receiver and transmitter via infrared signal
- Gain level adjustable in 4 steps
- Powered by a battery/battery pack
- Operating range up to 60m with line-of-sight
- License-free in Germany for professional use
- Up to 12 transmitters can be operated in parallel without interference
- Ultra-low latency
- LCD display
- Charge status indicator
- **microphone**
- Polar pattern: Cardioid

### Logistic

EAN / GTIN: 4026397738766

Weight: 0,16 kg

Length: 0.18 m

Width: 0.13 m

Height: 0.04 m

### Technical specifications:

|                      |                                    |
|----------------------|------------------------------------|
| Type:                | Bodypack with microphone           |
| Power supply:        | 3V DC 155 mA                       |
| Battery:             | 2 x Mignon (AA) (not included)     |
| Phantom power:       | 2.48 V DC                          |
| Range:               | Range up to 60m with line-of-sight |
| Frequency band:      | UHF 520 - 554 MHz                  |
| Switching bandwidth: | 34 MHz                             |

|                   |                                                                                     |
|-------------------|-------------------------------------------------------------------------------------|
| Parallel mode:    | Max. 12 transmitter                                                                 |
| RF power output:  | 20 mW (LO); 30 mW (HI)                                                              |
| Latency:          | < 3 ms                                                                              |
| Modulation:       | FM                                                                                  |
| Housing color:    | Black                                                                               |
| Display type:     | LCD display                                                                         |
| Display reading:  | Frequency , charge status indicator , Mute , RF signal level; AF audio level , gain |
| Control elements: | Gain-switch (high-mid-low)                                                          |
| Connections:      | Input: microphone via 1 x mini XLR (M) 3-pin mounting version                       |
| Switch:           | On/off switch; mute control                                                         |
| Material:         | Plastic                                                                             |
| Color:            | Black                                                                               |
| Dimensions:       | Width: 6.6 cm<br>Depth: 2.8 cm<br>Height: 8.5 cm                                    |
| Weight:           | 0.074 kg                                                                            |
| Type:             | Headset microphone                                                                  |
| Power supply:     | 1.5-10V DC                                                                          |
| Cable length:     | 1.0 m                                                                               |
| Capsule type:     | Condenser<br>Size: Ø 12 mm x 26.5 mm                                                |
| Polar pattern:    | Cardioid                                                                            |
| Frequency range:  | 80 - 18000 Hz                                                                       |
| Sensitivity:      | -53 dB                                                                              |
| Impedance:        | 600 Ohm                                                                             |
| Color:            | Skin-colored                                                                        |
| Weight:           | 0.028 kg                                                                            |

## Scope of delivery:

1 x transmitter  
 1 x user manual  
 1 x declaration of conformity  
 1 x microphone