

OMNITRONIC VHF-450 Wireless Mic System

Complete 2-channel wireless microphone system

Art. No.: 13073009

GTIN: 4026397294484



Features:

- Set includes receiver unit and 2 hand-held microphones with integrated transmitter
- Receiver:
 - Non-diversity system with removable metal telescope antennas (BNC connection)
 - 2 channels with separate level control
 - Blue backlit LCD for channel, frequency, carrier and audio signal
 - 6.3 mm jack and XLR output per channel
 - 6.3 mm jack output for mixed signal
 - Jack cable included
 - 8.5 mW transmitting power
 - Indicator for power and low battery
 - Gain control
- License-free and approved in the EU (please check on a country-by-country basis)

receiver

- License free in germany
- (19") 48.3 cm rack installation 1 U

microphone

- Polar pattern: Cardioid
- Operating range up to 100m

Logistic

EAN / GTIN: 4026397294484

Weight: 3,60 kg

Length: 0.51 m

Width: 0.29 m

Heigh: 0.14 m

Technical specifications:

Type:	Wireless set
Weight:	3.05 kg
Power supply:	230 V AC, 50 Hz

	15V DC 350 mA
Power consumption:	5.00 W
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter
Number of channels:	2
S/N ratio:	>90 dB
Frequency band:	VHF
RF power output:	8.5 mW
Modulation:	F3F; FM
Connections:	Output: microphone via 2 x 6.3 mm plug (unbal.) Output: line via 1 x 6.3 mm plug (unbal.) Output: microphone via 2 x 3-pin XLR
Material:	Metal
Housing design:	(19") 48.3 cm rack installation 1 U
Power supply:	9V DC
Power connection:	Battery/battery pack
Capsule type:	Dynamic
Polar pattern:	Cardioid
Battery:	1 x 9.0 V E block 6F22 zinc carbon included
Frequency range:	45 - 15000 Hz
Range:	Range up to 100m
Carrier frequency:	211.700 GHz; 174.100 MHz
Frequency stability:	± 0.003 %
Frequency selection:	Fixed frequencies
Switch:	On/off switch; mute control
Dimensions:	Length: 24.5 cm Diameter: Ø 5 cm
Weight:	0.250 kg

Scope of delivery:

1 x receiver
 2 x antenna
 1 x external mains adapter
 2 x microphone
 1 x jack cable
 2 x mounting bracket
 1 x user manual
 1 x declaration of conformity