



Features:

Logistic

FUTURELIGHT DMH-32 RGBW LED Moving Head

LED moving head with one 32 W RGBW LED (4in1) and unique color effect prism

- Equipped with one 32 W quadcolor LED with RGBW colors
- Comparable to the light output of a 150 W discharge lamp
- Color effect prism: Not only the gobos, also the colors are split
- High PAN/TILT speed
- 16, 18 or 23 DMX channels selectable
- 5-facet prism
- Masterdimmer
- Color presets
- Stepless RGBW color changing
- Gobo wheel with 6 rotating gobos plus open
- All gobos can be interchanged
- With gobo shake function
- Exact positioning via 16 bit PAN/TILT movement resolution, dimmer intensity, colors
- Manual focus
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- Sound-controlled via built-in microphone

- Switch-mode power supply, automatic power supply adaption between 100 and 240 Volts without power selector
- Control board with graphic LCD and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- DMX-controlled operation or stand-alone operation with Master/Slave function
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After 8 devices the fixtures must have a renewed connection with the power mains
- DMX control via any standard DMX controller
- Can be operated in 16 CH mode
- Control via sound to light via microphone; RDM

EUROLITE TPC-10 Coupler, silver

Mounting coupler for 50 mm tube, maximum load WLL 150 kg

EUROLITE Safety Bond AG-15 4x1000mm up to 15kg

High-quality safety rope

- For securing loads over people
- Round strand rope 6 x 19 with fibre core
- With two thimbles
- Complies with DIN EN 12385-4:2008-06 and DIN 56927:2009-03
- Rope with thimble and connector
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

FUTURELIGHT DMH-32 RGBW LED Moving Head

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	60 W
Max. TILT movement:	270° positioning
Max. PAN movement:	630° positioning
Gobos:	Outside diameter 24mm Image diameter 19mm
DMX channels:	16
Control:	Sound to light via microphone; RDM
Fixtures available for:	LED PC-Control 512
Beam angle (1/2 peak):	12°
Color:	Black
Dimensions:	Width: 24.4 cm Depth: 20.8 cm Height: 34 cm
Weight:	7.40 kg
DMX channels:	16/18/23
DMX connection:	5-pin XLR
Sound-control:	via built-in microphone
LED type:	32 W QCL
LED number:	1

Beam angle:	12°
Rotating gobo-wheel:	6 gobos and open
Outside diameter of the gobos:	24 mm
Image diameter of the gobos:	19 mm
Maximum PAN-movement:	630°
Maximum TILT-movement:	270°
Dimensions (L x W x H):	244 x 208 x 340 mm

EUROLITE TPC-10 Coupler, silver

Maximum load BGV C1 (8-fold):	75 kg
Maximum load WLL (4-fold):	150 kg
Tube diameter sector:	48 - 50 mm
Material:	Aluminum
Color:	Silver
Mounting screw:	M10
Dimensions:	Length: 10 cm Width: 3 cm Depth: 9 cm
Weight:	0.16 kg

EUROLITE Safety Bond AG-15 4x1000mm up to 15kg

Secured weight (BGV C1):	Max. 15 kg
Design of the core:	6 x 19 FC
Strength classification:	1770
Standard:	DIN EN 12385-4:2008-06, DIN 56927:2009-03
Nominal tensile strenght of rope:	1770 N/mm²
Wire surface:	Zinc-plated
Color:	Silver
Temperature range:	-40° C - +100° C
Dimensions:	Length: 100 cm Diameter: Ø 0.40 cm
Weight:	0.10 kg
Length weigth:	0.0554 kg/m

Scope of delivery:

1 x safety bond
1 x connector