



### Features:

### Logistic

#### EUROLITE AKKU UP-4 QCL Spot

Bright Uplight with 4 x 8 W 4in1 LED

- Compact and bright
- Equipped with 4 x 8 W QCL LED in red, green, blue and white
- Operation via mains connection or built-in rechargeable lithium-ion battery with up to 8.5 hours operating time
- Integrated automatic charging of the battery with indicator
- Controllable via EUROLITE IR-7 remote control; included in the delivery
- With integrated folding foot for flexible placement
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 4, 6 or 10 DMX channels selectable
- Functions: static colors, stepless RGBW color mixture, internal programs, dimmer, strobe effect with variable speed, sound-control
- Dimmer speed (step response) adjustable
- Adjustable microphone sensitivity
- Addressing via control panel with 4-digit LED display
- Switch-mode power supply for operation between 100 and 240 volts
- Ready for connection via included power cable with safety power plug
- Feed-through output allows to power up to 8 devices
- DMX control via any standard DMX controller
- 4 LEDs 8 W SMD 9080 4in1 RGBW (homogenous color mix)

- Can be operated in 4; 6; 10 CH mode
  - The device is cooled by passive convection cooling
  - Control via DMX; stand-alone; sound to light via microphone
  - Flicker-free
  - With a beam angle of 13°
- device**
- Cordless, flexible and versatile
  - Battery operation up to 8.5h depending on program used

#### ROADINGER Flightcase 4x AKKU UP-4

Trunk case, PRO version

- Cable bushing allows loading the devices inside
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Closes with a
- Rubber feet
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

#### Technical specifications:

|         |          |
|---------|----------|
| Weight: | 16.19 kg |
|---------|----------|

#### EUROLITE AKKU UP-4 QCL Spot

|                         |                                                                                                                                |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz                                                                                                         |
| Power consumption:      | 45.00 W                                                                                                                        |
| Power connection:       | Battery/battery pack<br>Mains input via IEC connector (M) mounting<br>version power supply cord with safety plug<br>(provided) |
| Power output:           | 1 x IEC connector (F) mounting version                                                                                         |
| Lamp type:              | LED lamp                                                                                                                       |
| LED type:               | 4 x 8 W SMD 9080 4in1 RGBW (homogenous<br>color mix)                                                                           |
| DMX channels:           | 4; 6; 10                                                                                                                       |
| DMX input:              | 1 x 3-pin XLR (M) mounting version                                                                                             |
| DMX output:             | 1 x 3-pin XLR (F) mounting version                                                                                             |
| Cooling:                | Passive convection cooling                                                                                                     |
| Control:                | DMX; stand-alone; sound to light via microphone                                                                                |
| Fixtures available for: | Light´J; LED PC-Control 512; Light Captain                                                                                     |
| Projection:             | Flicker-free                                                                                                                   |
| Beam angle:             | 13°                                                                                                                            |
| Beam angle (1/2 peak):  | 13°                                                                                                                            |
| Beam angle (1/10 peak): | 28.5°                                                                                                                          |

|                    |                                                                              |
|--------------------|------------------------------------------------------------------------------|
| Housing color:     | Black                                                                        |
| Dimensions:        | Width: 13.8 cm<br>Depth: 14.5 cm<br>Height: 19.1 cm                          |
| Weight:            | 2.90 kg                                                                      |
| Battery pack type: | 1 x lithium ion 14.8 V, 6600 mAh, 97.68 Wh                                   |
| Battery pack:      | Battery operation up to 8.5h depending on program used<br>Recharging time 5h |
| Battery:           | 1 x button cell 3.0 V CR2025 lithium manganese built-in                      |

#### **ROADINGER Flightcase 4x AKKU UP-4**

|                          |                                                 |
|--------------------------|-------------------------------------------------|
| Maximum load:            | 25 kg                                           |
| Aluminum profile frames: | 25 mm                                           |
| Case handle:             | 1 pc/pcs                                        |
| Stop hinge:              | 2 pc/pcs                                        |
| Lock:                    | Butterfly lock: 1 pc/pcs                        |
| Transport aid:           | Rubber feet                                     |
| Use of brands:           | Branded hardware                                |
| Material:                | Birch multiplex, 7 mm                           |
| Color:                   | Dark brown, laminated                           |
| Compartment dimensions:  | 16 cm x 15 cm x 15.5 cm                         |
| Inside dimensions:       | 33 cm x 31 cm x 15.5 cm                         |
| Dimensions:              | Width: 37 cm<br>Depth: 35 cm<br>Height: 25.5 cm |
| Weight:                  | 4.59 kg                                         |

#### **Scope of delivery:**

1 x device  
1 x remote control