



The article is no longer in our assortment.

Features:

Logistic

EUROLITE AKKU UP-4 HCL Spot WDMX wh

LED Uplight with 4 x 12 W 6in1 LED & wireless DMX receiver (Wireless Solution)

- Compact and bright
- Equipped with 4 x 12 W HCL LED in red, green, blue, amber, white and UV
- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- Operation via mains connection or built-in rechargeable lithium-ion battery with up to 8.5 hours operating time
- Integrated automatic charging of the battery with indicator
- Controllable via EUROLITE IR-7 remote control; included in the delivery
- With integrated folding foot for angled placement by floor installation
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 6, 8 or 12 DMX channels selectable
- Functions: static colors, stepless RGBAW+UV color mixture, internal programs, dimmer, strobe effect with variable speed, sound-control
- Dimmer speed (step response) adjustable
- Adjustable microphone sensitivity
- Addressing via control panel with 4-digit LED display
- Switch-mode power supply for operation between 100 and 240 volts
- Ready for connection via included power cable with safety power plug
- Feed-through output allows to power up to 8 devices
- DMX control via any standard DMX controller

- Available in 2 housing colors: black and white
 - 4 LEDs 12 W high-power 6in1 RGBWA/UV (homogenous color mix)
 - Can be operated in 6; 8; 12 CH mode
 - The device is cooled by passive convection cooling
 - Control via DMX; stand-alone; W-DMX by wireless solution; sound to light via microphone
 - Flicker-free
 - With a beam angle of 22°
- device**
- Cordless, flexible and versatile
 - Battery operation up to 8.5h depending on program used

ROADINGER Flightcase 8x AKKU UP-4

Trunk case, PRO version

- Cable bushing allows loading the devices inside
- With 8 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Closes with a
- Rubber feet
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	31.80 kg
---------	----------

EUROLITE AKKU UP-4 HCL Spot WDMX wh

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	37 W
Power connection:	Battery/battery pack Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	4 x 12 W high-power 6in1 RGBWA/UV (homogenous color mix)
DMX channels:	6; 8; 12
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; W-DMX by wireless solution; sound to light via microphone
Fixtures available for:	Light´J; LED PC-Control 512
Projection:	Flicker-free
Carrier frequency:	2.4 GHz

Beam angle:	22°
Beam angle (1/2 peak):	22°
Housing color:	White
Dimensions:	Width: 13.8 cm Depth: 14.5 cm Height: 19.1 cm
Weight:	2.90 kg
Battery pack type:	1 x lithium ion 14.8 V, 6600 mAh, 97.68 Wh
Battery pack:	Battery operation up to 8.5h depending on program used Recharging time 4.5h
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

ROADINGER Flightcase 8x AKKU UP-4

Maximum load:	50 kg
Aluminum profile frames:	25 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	Rubber feet
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Compartment dimensions:	16 cm x 15 cm x 15.5 cm
Inside dimensions:	66.5 cm x 31 cm x 15.5 cm
Dimensions:	Width: 70.5 cm Depth: 35 cm Height: 25.5 cm
Weight:	8.60 kg

Scope of delivery:

1 x device
1 x remote control