

EUROLITE Set 4x LED PAR-64 HCL 12x10W bk + Case

4 LED spots with matching PRO flightcase

Art. No.: 20000046

GTIN:



Features:

- 12 LEDs 10 W high-power 6in1 RGBWA/UV (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect; UV effect
- 3 integrated show programs
- Direct color selection for 15 preset colors
- Can be operated in 4; 10 CH mode
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; sound to light via microphone; IR remote control
- With a beam angle of 33°
- With double bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; stage; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended; on stand
- <p>ROADINGER Flightcase 4x PAR-64 Spot short

Trunk case, PRO version

- Detachable compartments - case can also be used as universal transport case
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Closes with a

Logistic

- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	21.85 kg
---------	----------

EUROLITE LED PAR-64 HCL 12x10W Floor bk

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	125 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	12 x 10 W high-power 6in1 RGBWA/UV (homogenous color mix)
DMX channels:	4; 10
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; sound to light via microphone; IR remote control
Fixtures available for:	Light´ J; LED PC-Control 512; LED EASY OPERATOR DELUXE; LED EASY OPERATOR 4x6; Light Captain
Beam angle:	33°
Beam angle (1/2 peak):	33°
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 29.6 cm Depth: 27.7 cm Height: 37.5 cm
Weight:	2.80 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

ROADINGER Flightcase 4x PAR-64 Spot short

Maximum load:	50 kg
---------------	-------

Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	23 cm x 23 cm x 32.5 cm
Inside dimensions:	46 cm x 46 cm x 32.5 cm
Dimensions:	Width: 51 cm Depth: 51 cm Height: 41.5 cm
Weight:	10.65 kg

Scope of delivery:

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 1 x remote control
- 1 x battery