




Features:

Logistic

EUROLITE LED KLS Laser Bar PRO FX Light Set

Bar with 2 strong derbies and spots, white/UV strobe LEDs, laser (RG, 2M)

- Enhanced version with very high brightness and additional UV LEDs
- Compact lightweight
- Crossbar with integrated DMX control unit and stand sleeve
- 2 laser diodes project hundreds of red and green laser beams
- 2 rotating derbies for mirror ball effects
- When fog is used, this effect becomes especially attractive
- Laser; multi beam effect; flower effect; UV effect; strobe effect
- 39 integrated show programs
- Can be operated in 3; 5; 10; 28 CH mode
- The device is cooled by cooling fan
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/slave function
- With mounting bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer; party room; restaurants, bars and hotels
- Application possibility: Suspended; on stand

laser

- Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer
- spotlight**
- 6 LEDs 6 W SMD 8072 3in1 RGB (homogenous color mix)
 spots controlled separately
- With a beam angle of 13°
- light effect**
- 6 LEDs 2 W SMD 8072 R/G/B
 spots controlled separately
- bar**
- 4 LEDs 2 W SMD 8072 2in1 CW/UV (homogenous color mix)
 LEDs controlled separately

OMNITRONIC M-2 Speaker-System Stand

Simple speaker stand, extendible up to 183 cm, maximum load 30 kg

- Height adjustable, with locking pin
- Adjustable height

Technical specifications:

Weight:	12.40 kg
---------	----------

EUROLITE LED KLS Laser Bar PRO FX Light Set

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	150 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 3.15 A
Lamp type:	LED lamp
DMX channels:	3; 5; 10; 28
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; wireless footswitch; master/slave function
Fixtures available for:	EASY SHOW 1; Light´J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Housing color:	Black
Attachment system:	Tube: 1x Ø 35mm 2x mounting bracket
Dimensions:	Width: 1.030 cm Depth: 6.1 cm Height: 38.7 cm
Weight:	10.00 kg
Noise classification:	Class 2 (slight noise)
Cable length:	3 m

Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Battery:	1 x 9.0 V E block 6F22 zinc carbon included
Laser class:	2M
Laser color:	R/G
Laser module:	Red (R) 100 mW 650nm Green (G) 30 mW 532nm
LED type:	6 x 2 W SMD 8072 R/G/B
Flash rate:	0 - 30 Hz
LED type:	6 x 6 W SMD 8072 3in1 RGB (homogenous color mix)
Beam angle:	13°
Beam angle (1/2 peak):	13°
Beam angle (1/10 peak):	20°
LED type:	4 x 2 W SMD 8072 2in1 CW/UV (homogenous color mix)
Flash rate:	0 - 30 Hz

OMNITRONIC M-2 Speaker-System Stand

Maximum carrying capacity:	30 kg
Height:	Maximum: 183 cm Minimum: 100 cm
Attachment system:	Ø 35mm
Type (general stands):	Speaker stand/manual
Material:	Steel
Color:	Black
Weight:	2.40 kg

Scope of delivery:

1 x EUROLITE LED KLS Laser Bar PRO FX Light Set

1 x device
 1 x power cord
 1 x user manual
 1 x declaration of conformity
 1 x remote control
 1 x foot control
 2 x knurled screw
 2 x washer
 2 x mounting bracket
 2 x battery
 1 x bag

1 x OMNITRONIC M-2 Speaker-System Stand

1 x stand
 1 x user manual