

EUROLITE Set PAR-16 Spot wh + GU-10 230V COB 7W 6400K

PAR-16 housing with GU-10 socket including special lamp for show effect lighting

Art. No.: 20000106

GTIN:



The article is no longer in our assortment.

Features:

- Mini-spot for GU-10 lamp
 - Color-filters attachable
 - Control via plug and play
 - For PAR 16
 - For application areas such as: Clubs/dancing school; decoration; Trade fair and shop fitting; party room; restaurants, bars and hotels; advertisement/Shop window
 - Silent operation
 - <p>OMNILUX GU-10 230V COB 7W 6400K
- Special lamp for show effect lighting**
- Spare lamp for Eurolite PAR-16 spots: 50850340 EUROLITE PAR-16 Spot GU-10 silver, 50850350 EUROLITE PAR-16 Spot GU-10 black, 50850352 EUROLITE PAR-16 Spot GU-10 white
 - Hot restrike
 - For further information about this product, please refer to the Data Sheet under "Downloads"

Logistic

Technical specifications:

Weight: 0.34 kg

EUROLITE PAR-16 Spot GU-10 white

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 75 W
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 0.75 mm ² H05SS-F
Cable length:	Approx. 0.4 m
Base:	GU10
Lamp type:	Selectable
Color generation:	Via color filter frame
Control:	Plug and play
Construction:	PAR-16
Housing color:	White
Material:	Aluminum, 1 mm
Slot for spot length:	7.8 cm x 7.8 cm
Dimensions:	Length: 17 cm Width: 11 cm Height: 13 cm
Weight:	0.30 kg
Noise classification:	Class 0 (no noise at all)
Diameter mounting holes:	2 x Ø10mm
Material:	Aluminum, 3 mm
Shape:	Octagonal
Material:	Aluminum
Dimensions:	Length: 7.7 cm Width: 7.7 cm Diameter: Ø 5.3 cm
Weight:	0.01 kg

OMNILUX GU-10 230V COB 7W 6400K

Voltage (lamps):	230 V, AC
Nominal wattage:	7 W
Base:	GU10
Lamp type:	LED lamp; clear lamp; high voltage lamp
Lamp specification:	Hot restrike
Beam angle:	90°
Color of light:	White
Color temperature:	6400K
Lead time:	1 s
Construction:	Reflector; bi pin
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	30000 h
Luminous flux:	550 lm

Lamp current:	0.06 A
Dimensions (LxD):	72x51 mm
Weight:	0.04 kg

Scope of delivery:

1 x spotlight
1 x filter frame
1 x user manual