



Features:

Logistic

EUROLITE PAR-38 Spot sil

PAR-38 housing with E27 socket (with plug + cable)

- Heat-resistant fixing screw
- Precise light output
- Strong cable tension relief
- Control via plug and play
- With mounting bracket
- For PAR 38
- For application areas such as: Clubs/dancing school; decoration; restaurants, bars and hotels; video and photography; advertisement/Shop window
- Silent operation

OMNILUX PAR-38 230V SMD 15W E-27 LED 2700K

PAR-38 lamp

- Easy installation
- Good color rendering index (CRI)

Technical specifications:

Weight:	1.06 kg
---------	---------

EUROLITE PAR-38 Spot sil

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 85 W
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable length:	Approx. 0.9 m
Base:	E27
Lamp type:	Selectable
Color generation:	Via color filter frame
Control:	Plug and play
Construction:	PAR-38
Housing color:	Silver
Attachment system:	Mounting bracket
Material:	Aluminum
Slot for spot length:	17.2 cm x 17.2 cm
Dimensions:	Width: 19 cm Depth: 19 cm Height: 21.5 cm
Weight:	0.70 kg
Noise classification:	Class 0 (no noise at all)
Diameter mounting holes:	2 x Ø12mm
Material:	Aluminum, 2 mm
Diameter mounting holes:	2 x Ø8mm
Material:	Aluminum
Dimensions:	Length: 17 cm Width: 17 cm Diameter: Ø 14 cm
Weight:	0.05 kg

OMNILUX PAR-38 230V SMD 15W E-27 LED 2700K

Operating voltage:	230 V
Nominal wattage:	15 W
Base:	E27
Lamp type:	LED lamp; reflector lamp
Beam angle:	60°
Setup:	Easy installation

Color of light:	White
Color temperature:	2700K
Color rendering index (CRI):	81 Ra
Lead time:	0.2 s
Construction:	PAR-38
Burning position:	S180 (universal)
Lamp life:	20000 h
Luminous flux:	1250 lm
Wavelength:	608 nm
Lamp current:	0.155 A
Dimensions (LxD):	135x121 mm
Weight:	0.36 kg
Energy efficiency class (A - G):	F
EPREL-Nr:	1042577

Scope of delivery:

1 x EUROLITE PAR-38 Spot sil

1 x spotlight
1 x filter frame
1 x user manual

1 x OMNILUX PAR-38 230V SMD 15W E-27 LED 2700K

1 x illuminant