

EUROLITE Set DMX LED Operator 6 + 4x LED PS-4 HCL spot

6 color spots (RGBWA+UV) with perfectly matching operator

Art. No.: 20000110

GTIN:



The article is no longer in our assortment.

Features:

- DMX controller for easy operation of standard 6-channel LED spots
- 6 spots or light effect units with RGBWA+UV LEDs can be controlled
- 6 DMX channels (red/green/blue/white/amber/UV) can be controlled per unit
- Sequence of white and amber function freely selectable
- 6 trigger buttons for direct color selection and preset chases
- 18 trigger buttons for color presets
- Internal memory for 1 scene
- Auto, fade and macro mode
- Fade and speed time can be adjusted separately
- Master fader
- Strobe function with adjustable speed
- Blackout function
- Desktop console
- Can transmit up to 36 DMX channels
- Control via DMX; sound to light via microphone
- Desktop console housing
- <p>EUROLITE LED PS-4 HCL Spot
- **Compact, fanless spot with 12 W 6in1 LEDs (RGBWA+UV)**
- Operable in stand-alone mode or via DMX
- Adjustable microphone sensitivity via control board
- Functions: Static colors, RGBWA+UV color mixture, UV effects, auto mode, internal programs, dimmer and strobe settings via DMX, Master/Slave
- Equipped with 4 x 12 W LEDs in red, green, blue, amber, white and UV
- Designed for hanging or standing installation
- Comfortable addressing and setting via control board with LED display and four operating buttons

Logistic

- Additional controlling possibility via the EUROLITE IR-7 remote control, included in delivery
- IEC terminals for power linking up to 8 units
- Switch-mode power supply for operation between 100 and 240 volts
- 4 LEDs 12 W high-power 6in1 RGBWA/UV (homogenous color mix)
- Strobe effect; UV effect
- Can be operated in 4; 10 CH mode
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; sound to light via microphone
- With a beam angle of 23°
- Silent operation

Technical specifications:

Weight:	8.71 kg
---------	---------

EUROLITE DMX LED Operator 6 Controller

Power supply:	100-240 V AC, 50/60 Hz
Pin configuration:	Inside + / outside -
Power consumption:	4 W
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
DMX channels:	Output 36
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; sound to light via microphone
Housing color:	Black
Color:	Black
Housing design:	Desktop console housing
Dimensions:	Width: 40 cm Depth: 15 cm Height: 7 cm
Weight:	1.60 kg

EUROLITE LED PS-4 HCL Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	33 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	4 x 12 W high-power 6in1 RGBWA/UV (homogenous color mix)
DMX channels:	4; 10
DMX input:	1 x 3-pin XLR (M) mounting version

DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone
Fixtures available for:	Light´J; LED PC-Control 512; Light Captain
Beam angle:	23°
Beam angle (1/2 peak):	23°
Beam angle (1/10 peak):	42°
Housing color:	Black
Dimensions:	Width: 18.9 cm Depth: 11.7 cm Height: 19.6 cm
Weight:	1.78 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

Scope of delivery:

1 x spotlight
 1 x user manual
 1 x power cord
 1 x remote control
 1 x battery