EUROLITE Set TMH XB-200 Moving-Head-Beam + OSD 5

Art. No.: 20000150

GTIN:









Features:

EUROLITE TMH XB-200 Moving Head Beam

High performance beam for 200 W discharge lamp

- Very narrow beam angle with 2°
- With electronic ballast
- Color wheel with 13 different dichroic color filters plus white
- Switchable color change (mode 1: only full colors, mode 2: half colors)
- Rainbow effect with adjustable speed
- 8-facet prism
- Frost-filter
- Gobo wheel with 13 static gobos plus open
- With gobo shake function
- Motorized focus
- Strobe effect with adjustable speed
- Random strobe effect
- Dimmer
- Exact positioning via 16 bit PAN/TILT movement resolution
- Automatic position correction
- Switch-mode power supply for operation between 100 and 240 volts
- Control board with graphic LC display and encoder for adjusting the DMX-starting address, PAN/TILT reverse, reset, lamp on/off, operating hours
- DMX-controlled operation or stand-alone operation with master/slave function

Logistic

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

- For OSD 5 Reflector 200 W discharge lamp
- Power connection via Neutrik PowerCon socket and included power cable
- DMX-control via every standard DMX-controller

OMNILUX OSD 5 Reflector 200W Discharge Lamp

OMNILUX OSD technology

- Very short arc
- Compact design
- Reflector lamp
- High beam intensity
- Freedom to create smaller and lighter fixtures
- Perfect alignment and placing with lamp replacements in seconds
- Renewed optical system with maximum light output
- High perceived brightness
- Dimmable
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	12.87 kg

EUROLITE TMH XB-200 Moving Head Beam

Power supply:	100-240 V AC, 50/60 Hz
Fixtures available for:	LED PC-Control 512
Dimensions:	Width: 31 cm Depth: 25 cm Height: 38 cm
Power consumption:	250 W
DMX channels:	16
DMX connection:	3-pin XLR
Flash-rate:	1-10 Hz
Color-wheel:	13 dichroic filters plus open
Static gobo-wheel:	13 gobos and open
Maximum PAN-movement:	540°
Maximum TILT-movement:	270°
Beam angle:	2°
Dimensions (L x W x H):	250 x 310 x 380 mm
Weight:	12 kg

OMNILUX OSD 5 Reflector 200W Discharge Lamp

Operating voltage:	75 V
Nominal wattage:	200 W
Base:	Special
Lamp type:	Discharge lamp
Lamp specification:	Dimmable

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Color temperature:	8200K
Burning position:	S180 (universal)
Lamp life:	2000 h
Luminous flux:	8500 lm
Lamp current:	2.7 A
Dimensions (LxD):	61.5x51 mm
Weight:	0.07 kg
EPREL-Nr:	2033767

Scope of delivery:

1 x illuminant

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.