



Features:

Logistic

EUROLITE TMH XB-230 Moving-Head Beam

High performance beam for 230 W discharge lamp

- Very narrow beam angle with 3°
- With electronic ballast
- Color wheel with 14 different dichroic color filters plus white
- Switchable color change (mode 1: only full colors, mode 2: half colors)
- Rainbow effect with adjustable speed
- 8-facet prism
- Frost-filter
- Gobo wheel with 17 static gobos plus open
- With gobo shake function
- Motorized focus
- Strobe effect with adjustable speed
- Random strobe effect
- Dimmer
- Exact positioning via 16 bit PAN/TILT movement resolution
- Automatic position correction
- Switch-mode power supply for operation between 100 and 240 volts
- Control board with graphic LC display and encoder for adjusting the DMX-starting address, PAN/TILT reverse, reset, lamp on/off, operating hours
- DMX-controlled operation or stand-alone operation with master/slave function

- For OSD 7 Reflector 230 W discharge lamp
- Power connection via Neutrik PowerCon socket and included power cable
- DMX-control via every standard DMX-controller
- Gobos
- Beam effect
- The device is cooled by cooling fan
- Control via DMX; stand-alone
- With a beam angle of 3°

OMNILUX OSD 7 Reflector 230W Discharge Lamp

OMNILUX OSD technology

- Very short arc
- Compact design
- Reflector lamp
- Long life
- High beam intensity
- Freedom to create smaller and lighter fixtures
- Perfect alignment and placing with lamp replacements in seconds
- Renewed optical system with maximum light output
- High perceived brightness
- Dimmable
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	19.20 kg
---------	----------

EUROLITE TMH XB-230 Moving-Head Beam

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	300 W
Lamp type:	Discharge lamp
Equipment:	Gobos
Cooling:	Cooling fan
Control:	DMX; stand-alone
Fixtures available for:	LED PC-Control 512
Beam angle:	3°
Beam angle (1/2 peak):	3°
Housing color:	Black
Dimensions:	Width: 39.5 cm Depth: 32 cm Height: 51 cm
Weight:	19.14 kg
DMX channels:	16
DMX connection:	5-pin and 3-pin XLR
Flash-rate:	18 Hz
Color-wheel:	14 dichroic filters plus open
Static gobo-wheel:	17 gobos and open
Maximum PAN-movement:	540°

Maximum TILT-movement:	250°
Beam angle:	3°
Dimensions (L x W x H):	395 x 320 x 510 mm

OMNILUX OSD 7 Reflector 230W Discharge Lamp

Operating voltage:	75 V
Nominal wattage:	230 W
Base:	Special
Lamp type:	Discharge lamp
Lamp specification:	Dimmable
Color temperature:	8000K
Burning position:	S180 (universal)
Lamp life:	2000 h
Luminous flux:	10500 lm
Lamp current:	3.3 A
Dimensions (LxD):	61.5x51 mm
Weight:	0.06 kg
EPREL-Nr:	2033771

Scope of delivery: