

EUROLITE Set 2x LED PFE-100 RGBW + Case

2x PRO profile spotlight with 100 W 4in1 LED including PRO flightcase

Art. No.: 20000160

GTIN: 4026397586206



Features:

- 1 LED 100 W COB (chip-on-board) 4in1 RGBW
- Focus manual
- Control via stand-alone; DMX; master/slave function
- Dimmer electronic; color blend stepless; color change adjustable; Dimmer speed (step response) adjustable
- Strobe effect
- With mounting bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; wedding/gala/events; Trade fair and shop fitting; video and photography; theater; rental
- Application possibility: Suspended; on stand
- Can be operated in 9 CH mode
- With a beam angle of 14° - 41°
- <p>ROADINGER Flightcase 2x PFE-100/120
- **Trunk case with castors, PRO version**
- With accessory compartment
- With 2 device compartments
- High-quality workmanship with birch multiplex 7 mm, black, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Closes with a
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover

Logistic

EAN / GTIN: 4026397586206

Weight: 46,50 kg

Length: 0.80 m

Width: 0.60 m

Height: 0.60 m

Bulky product

- PENN Hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	50.90 kg
---------	----------

EUROLITE LED PFE-100 RGBW Profile Spot

Power supply:	100-240 V AC, 50/60 Hz
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (grey), mounting version
Lamp type:	LED lamp
LED type:	1 x 100 W COB (chip-on-board) 4in1 RGBW
Flash rate:	0.5 - 10 Hz
Equipment:	Focus manual
DMX channels:	9
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; master/slave function
Fixtures available for:	LED PC-Control 512; Light Captain
PWM frequency:	2300 Hz
Beam angle:	14° - 41°
Beam angle (1/2 peak):	14 - 41°
Beam angle (1/10 peak):	14 - 41°
Lamp life:	50000 h
Luminous flux:	11500 lm
Housing color:	Black matte
Attachment system:	Mounting bracket
Display type:	OLED display
Diameter mounting holes:	2 x Ø13mm
Material:	Aluminum casting; metal
Dimensions:	Length: 61.5 cm Width: 28 cm Height: 42 cm
Weight:	11.10 kg
Noise classification:	Class 2 (slight noise)
Energy efficiency class (A - G):	F
EPREL-Nr:	1243754
Cable construction:	3 x 1.5 mm² H05VV-F

Cable length:	Approx. 1.2 m
Diameter mounting holes:	1 x Ø12mm
Material:	Aluminum casting, 7 mm
Diameter mounting holes:	4 x Ø18mm
Material:	Aluminum, 1 mm
Dimensions:	Width: 19.5 cm Height: 20.5 cm Diameter: Ø 15.8 cm

ROADINGER Flightcase 2x PFE-100/120

Maximum load:	100 kg
Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Use of brands:	PENN Hardware
Material:	Birch multiplex, 7 mm
Color:	Black, laminated
Device compartment:	34 cm x 29 cm x 56 cm
Accessory compartment:	69 cm x 10.5 cm x 60 cm
Inside dimensions:	69 cm x 40 cm x 62 cm
Dimensions:	Width: 73 cm Depth: 44.5 cm Height: 88 cm
Weight:	26.30 kg

Scope of delivery:

1 x spotlight
 1 x power cord
 1 x filter frame
 1 x plug (male)
 1 x user manual