

EUROLITE Set 4x LED THA-250F + Case

4x Theater-Spot with fresnel spot including PRO flightcase

Art. No.: 20000162

GTIN: 4026397586220



List price: 4996.81 €

incl. 19% VAT.

Features:

- Very high color rendering index (CRI)
- With a beam angle of 5° - 38°
- Zoom motor driven; focus manual
- Flicker-free
- Control via RDM; stand-alone; DMX; quick select potentiometer for brightness and Zoom
- Dimmer electronic; dimmer curves with adjustable response; Dimmer speed (step response) adjustable
- Strobe effect
- 1 LED 200 W COB (chip-on-board) warm white (WW)
- With mounting bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; wedding/gala/events; Trade fair and shop fitting; theater; rental; video and photography
- Application possibility: Suspended; on stand
- Can be operated in 3 CH mode
- <p>ROADINGER Flightcase 4x THA-250F with wheels
- **Trunk case with castors, PRO version**
- With accessory compartment
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 3 chrome tip-over locks
- 2 high-quality butterfly locks
- Closes with a

Logistic

EAN / GTIN: 4026397586220

Weight: 70,00 kg

Length: 0.80 m

Width: 0.60 m

Height: 0.60 m

Bulky product

- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	81.30 kg
---------	----------

EUROLITE LED THA-250F Theater Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	265 W
Protection class:	Protection class I
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (grey), mounting version
Fuse:	5 x 20 mm, T 3 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 200 W COB (chip-on-board) warm white (WW)
Flash rate:	1.5 - 12 Hz
Equipment:	Zoom motor driven; focus manual
DMX channels:	3
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	RDM; stand-alone; DMX; quick select potentiometer for brightness and Zoom
Fixtures available for:	LED PC-Control 512; Light Captain; Light J
Projection:	Flicker-free
PWM frequency:	3600 Hz
Beam angle:	5° - 38°
Beam angle (1/2 peak):	5 - 28°
Beam angle (1/10 peak):	12 - 38°
Color temperature:	2800K
Color rendering index (CRI):	92 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Transport aid:	Rubber feet
Dimensions:	Length: 45.7 cm

	Width: 33.6 cm Height: 39.9 cm
Weight:	10.00 kg
Noise classification:	Class 2 (slight noise)

ROADINGER Flightcase 4x THA-250F with wheels

Maximum load:	100 kg
Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	3 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Accessory compartment:	11 cm x 81 cm x 30 cm
Device compartment:	49.5 cm x 20 cm x 27 cm
Inside dimensions:	110 cm x 81 cm x 30 cm
Dimensions:	Width: 116 cm Depth: 86 cm Height: 55 cm
Weight:	32.60 kg

Scope of delivery:

1 x spotlight
 1 x user manual
 1 x power cord
 1 x barndoor
 1 x filter frame