

EUROLITE Set 4x LED THA-40PC wh + Case

4x fanless Pc spot including PRO flightcase with wheels

Art. No.: 20000167

GTIN: 4026397586275



Features:

- Very high color rendering index (CRI)
- Silent operation
- Flicker-free
- Control via RDM; stand-alone; DMX
- Dimmer electronic; dimmer curves with adjustable response; Dimmer speed (step response) adjustable
- Strobe effect
- 1 LED 57 W COB (chip-on-board) warm white (WW)
- The device is cooled by passive convection cooling
- With mounting bracket
- For application areas such as: Stage; decoration; wedding/gala/events; Trade fair and shop fitting; restaurants, bars and hotels; theater; video and photography; advertisement/Shop window
- Application possibility: Suspended; on stand
- Can be operated in 1; 2 CH mode
- With a beam angle of 11° - 48°
- <p>ROADINGER Flightcase 4x THA-40 PC with wheels
- **Trunk case with castors, PRO version**
- With accessory compartment
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks

Logistic

EAN / GTIN: 4026397586275

Weight: 34,54 kg

Length: 1.20 m

Width: 0.60 m

Height: 0.60 m

Bulky product

- Closes with a
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	32.12 kg
---------	----------

EUROLITE LED THA-40PC Theater Spot wh

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	40 W
Power connection:	Fixed power supply cord with safety plug
Lamp type:	LED lamp
LED type:	1 x 57 W COB (chip-on-board) warm white (WW)
DMX channels:	1; 2
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	RDM; stand-alone; DMX
Fixtures available for:	LED PC-Control 512; Light Captain; Light´J; Colorchief
Projection:	Flicker-free
Beam angle:	11° - 48°
Beam angle (1/2 peak):	11 - 37°
Beam angle (1/10 peak):	17 - 48°
Color temperature:	3100K
Color rendering index (CRI):	91 Ra
Illuminance in Lux (lx):	Warm white (WW) 3m: 1656 lx, 6m: 424 lx
Housing color:	White
Attachment system:	Mounting bracket
Display type:	LCD display
Transport aid:	Rubber feet
Dimensions:	Length: 27.5 cm Width: 20.5 cm Depth: 25 cm
Weight:	3.84 kg
Noise classification:	Class 0 (no noise at all)

ROADINGER Flightcase 4x THA-40 PC with wheels

Maximum load:	100 kg
---------------	--------

Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	31 cm x 13 cm x 15 cm
Accessory compartment:	9.5 cm x 47 cm x 18 cm
Inside dimensions:	71.5 cm x 47 cm x 18 cm
Dimensions:	Width: 78 cm Depth: 52 cm Height: 42.5 cm
Weight:	16.75 kg

Scope of delivery:

1 x spotlight
1 x user manual
1 x barndoor