



Features:

Logistic

EUROLITE LED TMH-X12 Moving-Head Spot

Bright spot with 120 W LED, rotating gobos, color wheel and prism

- 1 LED 120 W COB (chip-on-board) cold white (CW)
- Positioning within 540° PAN, 270° TILT
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Gobo wheel with rotating gobos; prism 3-fold; focus motor-driven
- Dimmer electronic
- Multi beam effect; gobo effect; strobe effect
- Color wheel with 8 dichroic filters plus open
half colors selectable, Rainbow effect with adjustable speed
- Gobo wheel with rotating gobos, 7 gobos and open
shake effect
- Gobos changeable
- Slot-in gobo system for easy gobo replacement
- Integrated show programs
- Can be operated in 13; 15 CH mode
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone
- Flicker-free
- With a beam angle of 12°
- LCD display

- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; stage; rental
- Application possibility: Standing; suspended

ROADINGER Flightcase 2x TMH-X12 with wheels

PRO flightcase for 2 x TMH-X12

- Fitted for two devices and accessory
- Additional accessory compartment
- Interior upholstered with foam
- High-quality workmanship with birch multiplex, dark brown laminated
- Aluminum profile frames (25 mm) with rounded edges
- Three-leg, big steel ball corners
- Lid with 2 tip-over locks
- 4 castors (100 mm), 2 of which with locking brakes
- 2 chrome butterfly locks
- 2 chrome case handles
- 4 stacking dishes for stacking the cases
- Castors
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	41.50 kg
---------	----------

EUROLITE LED TMH-X12 Moving-Head Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	170 W
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (grey), mounting version
Fuse:	5 x 20 mm, T 2 A fuse replaceable
Lamp type:	LED lamp
LED type:	1 x 120 W COB (chip-on-board) cold white (CW)
Max. TILT movement:	270° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	0 - 18 Hz
Equipment:	Gobo wheel with rotating gobos; prism 3-fold; focus motor-driven
Color generation:	Color wheel with 8 dichroic filters plus open Half colors selectable, Rainbow effect with adjustable speed
Gobos:	Gobo wheel with rotating gobos, 7 gobos and open Outside diameter 23.5mm Image diameter 15mm

	Shake effect Gobos changeable Slot-in gobo system for easy gobo replacement
DMX channels:	13; 15
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; sound to light via microphone
Fixtures available for:	Light´J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle:	12°
Beam angle (1/2 peak):	12°
Illuminance in Lux (lx):	Cold white (CW) 3m: 9502 lx, 6m: 2436 lx
Housing color:	Black
Display type:	LCD display
Dimensions:	Width: 33 cm Depth: 32 cm Height: 40 cm
Weight:	11.35 kg
Noise classification:	Class 3 (clearly perceptible sounds)

ROADINGER Flightcase 2x TMH-X12 with wheels

Maximum load:	50 kg
Transport aid:	Castors
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Dimensions:	Width: 76.5 cm Depth: 42.5 cm Height: 79.5 cm
Weight:	18.80 kg
Inside dimensions (W x D x H):	705 x 380 x 400 mm
Compartment dimensions (W x D x H):	300 x 295 x 400 mm
Accessory compartment (W x D x H):	105 x 380 x 400 mm

Scope of delivery:

1 x moving light
1 x user manual
1 x power cord
2 x omega bracket