

EUROLITE Set 4x LED TMH-60 MK2 + Case

4x bright spot with 60 W LED including PRO flightcase with wheels

Art. No.: 20000189

GTIN:



The article is no longer in our assortment.

Features:

- Compact lightweight
- Equipped with a 60 W COB LED
- 3-facet prism (rotating)
- Preprogrammed scenes in Program Run for stand-alone operation
- Electronic dimmer
- Motorized focus
- Programmable color-change speed and strobe effect
- Exact positioning via 16 bit PAN/TILT movement resolution
- PAN-angle switchable between 540°, 360° and 180° (in sound and auto mode)
- TILT-angle switchable between 270°, 180° and 90° (in sound and auto mode)
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Control board with LC display and foil-keyboard for adjusting the DMX-starting address, PAN/TILT Reverse, Program, Reset
- Switch-mode power supply for operation between 100 and 240 Volts
- 1 LED 60 W COB (chip-on-board) cold white (CW)
- TILT angle switchable between 270° and 180°; and 90°
- PAN angle switchable between 540° and 360°; and 180°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Gobo wheel with rotating gobos; gobo wheel with static gobos; prism 3-fold; focus motor-driven
- Gobo effect; beam effect
- Color wheel with 7 dichroic filters plus open
rainbow effect with adjustable speed in both directions
- Gobo wheel with static gobos, 8 gobos and open
- Gobo wheel with rotating gobos, 6 gobos and open
shake effect
- Can be operated in 2; 11; 14 CH mode

Logistic

- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone
- With a beam angle of 14°
- LCD display
- <p>ROADINGER Flightcase 4x TMH-30/TMH-40/TMH-60 with wheels
- Trunk case with castors, PRO version**
- For optimal security
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Closes with a
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

EUROLITE LED TMH-60 MK2 Moving Head Spot COB

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	135 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	1 x 60 W COB (chip-on-board) cold white (CW)
Max. TILT movement:	270°, 180° exact positioning (16 bit resolution) auto position correction (feedback); , 90°
Max. PAN movement:	540°, 360° exact positioning (16 bit resolution) auto position correction (feedback); , 180°
Equipment:	Gobo wheel with rotating gobos; gobo wheel with static gobos; prism 3-fold; focus motor-driven
Color generation:	Color wheel with 7 dichroic filters plus open Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with static gobos, 8 gobos and open Gobo wheel with rotating gobos, 6 gobos and open Shake effect
DMX channels:	2; 11; 14
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; sound to light via microphone
Fixtures available for:	Light´J; LED PC-Control 512; EASY SHOW 1; Light Captain
Beam angle:	14°
Beam angle (1/2 peak):	14°

Illuminance in Lux (lx):	Cold white (CW) 1m: 26675 lx, 3m: 3045 lx, 6m: 768 lx
Housing color:	Black
Display type:	LCD display
Dimensions:	Width: 25 cm Depth: 24.5 cm Height: 31.5 cm
Weight:	7.40 kg

ROADINGER Flightcase 4x TMH-30/TMH-40/TMH-60 with wheels

Maximum load:	100 kg
Aluminum profile frames:	30 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	27 cm x 27 cm x 28 cm
Accessory compartment:	10 cm x 56 cm x 28 cm
Inside dimensions:	65 cm x 55 cm x 30.5 cm
Dimensions:	Length: 71 cm Width: 60 cm Height: 53 cm
Weight:	20.20 kg

Scope of delivery:

1 x moving light
 1 x user manual
 1 x power cord
 1 x XLR cable
 2 x omega bracket