



**The article is no longer in our assortment.**

### Features:

### Logistic

#### EUROLITE LED BAR-252 RGB 10mm 40° white

LED bar with 252 LEDs

- DMX512 control via regular DMX controller
- Sound-control via built-in microphone
- Stand-alone mode functions adjustable via DIP switches
- Color-change speed and strobe effect adjustable via DIP switches
- Multi-color color-changes
- Master/Slave function
- Ideal for bands, stages or solo entertainers
- Perfect in public places, main halls, lounges
- Illuminants: 252 10 mm LEDs (48 x red, 108 x green and 96 x blue)
- Available in 2 LED beam angles: 20° or 40°
- Advantages of LED technology: long life of the LEDs, low power consumption, minimal heat emission, defacto maintenance free with brilliant light radiation
- 252 LEDs 10 mm R/G/B
- Strobe effect
- Can be operated in 12 CH mode
- Control via stand-alone; DMX; sound to light via microphone
- With a beam angle of 40°

## ROADINGER Flightcase 4x LED BAR-252 RGB

Carrying case, PRO version

- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- Rugged carrying handle
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Closes with a
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

|         |          |
|---------|----------|
| Weight: | 18.30 kg |
|---------|----------|

## EUROLITE LED BAR-252 RGB 10mm 40° white

|                         |                                                 |
|-------------------------|-------------------------------------------------|
| Power supply:           | 230 V AC, 50 Hz                                 |
| Power consumption:      | 50.00 W                                         |
| Power connection:       | Fixed power supply cord with safety plug        |
| Lamp type:              | LED lamp                                        |
| LED type:               | 252 x 10 mm R/G/B                               |
| DMX channels:           | 12                                              |
| Control:                | Stand-alone; DMX; sound to light via microphone |
| Fixtures available for: | LED PC-Control 512                              |
| Beam angle:             | 40°                                             |
| Beam angle (1/2 peak):  | 40°                                             |
| Housing color:          | White                                           |
| Dimensions:             | Length: 107 cm<br>Depth: 6.5 cm<br>Height: 9 cm |
| Weight:                 | 2.25 kg                                         |
| DMX connection:         | 3-pin XLR                                       |

## ROADINGER Flightcase 4x LED BAR-252 RGB

|                          |                          |
|--------------------------|--------------------------|
| Maximum load:            | 25 kg                    |
| Aluminum profile frames: | 30 mm                    |
| Carrying handle:         | 1 pc/pcs                 |
| Stop hinge:              | 2 pc/pcs                 |
| Lock:                    | Butterfly lock: 2 pc/pcs |
| Use of brands:           | Branded hardware         |
| Material:                | Birch multiplex, 7 mm    |

|                     |                                                      |
|---------------------|------------------------------------------------------|
| Color:              | Dark brown, laminated                                |
| Inside dimensions:  | 106.5 cm x 44 cm x 7.5 cm                            |
| Device compartment: | 106.5 cm x 6.5 cm x 7.5 cm                           |
| Dimensions:         | Width: 114.5 cm<br>Depth: 47.5 cm<br>Height: 14.5 cm |
| Weight:             | 9.30 kg                                              |

**Scope of delivery:**