

EUROLITE Set 4x AKKU UP-1 + SB-4 Soft Bag + QuickDMX Wireless Transmitter

number: 20000267

GTIN: 4026397594744

4x LED uplight with black soft bag and wireless DMX transmitter



Features:

- Integrated QuickDMX transceiver for wireless DMX control
- Inclination angle of the LED head manually adjustable
- Interchangeable front lens for 9° or 15° beam angle
- Cordless, flexible and versatile
- Battery operation up to 18h depending on program used
- Integrated automatic charging of the battery and status indicator
- 1 LED 15 W SMD 9080 4in1 RGBW (homogenous color mix)
- Dimmer speed (step response) adjustable; colors preset; color blend stepless; color change adjustable; Dimmer electronic
- Strobe effect
- Can be operated in 3; 4; 6; 8; 10 CH mode
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; QuickDMX; sound to light via microphone; IR remote control
- Flicker-free
- With a beam angle of 9°
- For application areas such as: Decoration; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels; rental; advertisement/Shop window
- Silent operation
- Application possibility: Standing
- <p>EUROLITE SB-4 Soft Bag L
- **Black soft bag for up to 4 devices, 320 x 320 x 200 mm**
- Practical transport bag offers enough space for several lighting effects and accessories
- With dividers
- With 2 Outside pockets
- With 4 device compartments
- High-quality workmanship with nylon , black, water repellent

Logistic

EAN / GTIN: 4026397594744

Weight: 10,60 kg

Length: 0.82 m

Width: 0.41 m

Heigh: 0.52 m

- Interior with foam padding
cover with foam padding
- 2 carrying straps
- <p>EUROLITE QuickDMX Wireless Transmitter
- **Compact wireless DMX transmitter 2.4 GHz**
- User-friendly 3-pin XLR adapter (male) with swivel antenna
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX transceiver and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- 1 to 512 QuickDMX receivers can be controlled by each transmitter
- LED indication for functions
- Transceiver, to be used as transmitter or receiver
- Can transmit up to 512 DMX channels
- Control via QuickDMX; DMX; plug and play
- Operating range up to 400m
- Up to 6 transmitters can be operated in parallel without interference

Technical specifications:

Weight:	9.51 kg
---------	---------

EUROLITE AKKU UP-1 QCL Flex Spot QuickDMX

Power consumption:	15 W
Protection class:	Protection class III
Power connection:	Battery/battery pack Mains input via coaxial power connector (M) mounting version power supply cord with Euro plug (provided)
Battery pack type:	1 x lithium ion 7.4 V, 8800 mAh, 65.12 Wh
Battery pack:	Battery operation up to 18h depending on program used Recharging time 6h
Lamp type:	LED lamp
LED type:	1 x 15 W SMD 9080 4in1 RGBW (homogenous color mix)
DMX channels:	3; 4; 6; 8; 10
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; QuickDMX; sound to light via microphone; IR remote control
Fixtures available for:	Light´J; LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Carrier frequency:	2.4 GHz
Beam angle:	9°
Beam angle (1/2 peak):	9° 15°
Beam angle (1/10 peak):	18°

	30°
Housing color:	Black
Dimensions:	Width: 12 cm Depth: 12 cm Height: 14.2 cm
Weight:	2.21 kg
Noise classification:	Class 0 (no noise at all)
Power supply:	100-240 V AC, 50/60 Hz 8.4V 3000 mA
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in

EUROLITE SB-4 Soft Bag L

Maximum load:	25 kg
Carrying strap:	2 pc/pcs
Material:	Nylon
Color:	Black, water repellent
Compartment dimensions:	15 cm x 15 cm x 20 cm
Inside dimensions:	32 cm x 32 cm x 20 cm
Dimensions:	Width: 32 cm Depth: 41 cm Height: 20 cm
Weight:	0.52 kg

EUROLITE QuickDMX Wireless Transmitter

Power supply:	100-240 V AC, 50/60 Hz 5V DC 1000 mA
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord for USB A mains connection (provided)
DMX channels:	Output 512
DMX input:	1 x 3-pin XLR (M)
Control:	QuickDMX; DMX; plug and play
Range:	Range up to 400m
Carrier frequency:	2.4 GHz
Parallel mode:	Max. 6 transmitter
RF power output:	19 dBm
Modulation:	GFSK
Color:	Silver
Dimensions:	Length: 21.2 cm Diameter: Ø 1.8 cm
Weight:	0.15 kg

Scope of delivery:

4 x EUROLITE AKKU UP-1 QCL Flex Spot QuickDMX

- 1 x spotlight
- 1 x external mains adapter
- 1 x remote control
- 2 x battery
- 1 x lens
- 1 x omega bracket
- 1 x user manual
- 1 x power cord

1 x EUROLITE SB-4 Soft Bag L

- 1 x bag

1 x EUROLITE QuickDMX Wireless Transmitter

- 1 x device
- 1 x user manual
- 1 x declaration of conformity
- 1 x external mains adapter
- 1 x USB cable