



### Features:

### Logistic

#### EUROLITE AKKU TL-3 TCL Trusslight

Spotlight with 3 x 3 W 3in1 LED (RGB) for lighting within trussing

- Compact and bright, making it perfect for truss installation
- Cordless, flexible and versatile
- Equipped with 3 x 3 W TCL LED in red, green and blue
- Operation via mains connection or built-in rechargeable lithium-ion battery with up to 6.5 hours operating time
- Integrated automatic charging of the battery with indicator
- Controllable via EUROLITE IR-7 remote control; included in the delivery
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 3, 5 or 8 DMX channels selectable
- Functions: static colors, stepless RGB color mixture, internal programs, dimmer, strobe effect with variable speed, sound-control, Master/Slave operation
- Dimmer speed (step response) adjustable
- Adjustable microphone sensitivity
- Addressing via control panel with 4-digit LED display
- Ideal for booth construction, stages and any kind of truss
- Ideal for ALUTRUSS 3-POINT SYSTEM DECOLOCK DQ3
- Hanging as well as standing installation possible
- Switch-mode power supply for operation between 100 and 240 volts
- Ready for connection via included power cable with safety power plug

- Feed-through output allows to power up to 8 devices
  - 3 LEDs 3 W SMD 8072 3in1 RGB (homogenous color mix)
  - Can be operated in 3; 5; 8 CH mode
  - Control via DMX; stand-alone; sound to light via microphone
  - Flicker-free
  - With a beam angle of 16°
- device**
- Cordless, flexible and versatile
  - Battery operation up to 6.5h depending on program used

#### ROADINGER Flightcase 4x AKKU TL-3 TCL Trusslight

Carrying case, PRO version

- With accessory compartment
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Closes with a
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

#### Technical specifications:

|         |         |
|---------|---------|
| Weight: | 9.90 kg |
|---------|---------|

#### EUROLITE AKKU TL-3 TCL Trusslight

|                         |                                                                                                                                |
|-------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz                                                                                                         |
| Power consumption:      | 19.00 W                                                                                                                        |
| Power connection:       | Battery/battery pack<br>Mains input via IEC connector (M) mounting<br>version power supply cord with safety plug<br>(provided) |
| Power output:           | 1 x IEC connector (F) mounting version                                                                                         |
| Lamp type:              | LED lamp                                                                                                                       |
| LED type:               | 3 x 3 W SMD 8072 3in1 RGB (homogenous color mix)                                                                               |
| Flash rate:             | 0 - 30 Hz                                                                                                                      |
| DMX channels:           | 3; 5; 8                                                                                                                        |
| DMX input:              | 1 x 3-pin XLR (M) mounting version                                                                                             |
| DMX output:             | 1 x 3-pin XLR (F) mounting version                                                                                             |
| Control:                | DMX; stand-alone; sound to light via microphone                                                                                |
| Fixtures available for: | Light´J; LED PC-Control 512; Light Captain                                                                                     |
| Projection:             | Flicker-free                                                                                                                   |
| Beam angle:             | 16°                                                                                                                            |
| Beam angle (1/2 peak):  | 16°                                                                                                                            |
| Beam angle (1/10 peak): | 34°                                                                                                                            |

|                    |                                                                                |
|--------------------|--------------------------------------------------------------------------------|
| Housing color:     | Black                                                                          |
| Dimensions:        | Width: 12.1 cm<br>Depth: 10.8 cm<br>Height: 13.6 cm                            |
| Weight:            | 1.35 kg                                                                        |
| Battery pack type: | 1 x lithium ion 11.1 V, 4400 mAh, 48.84 Wh                                     |
| Battery pack:      | Battery operation up to 6.5h depending on program used<br>Recharging time 4.5h |
| Battery:           | 1 x button cell 3.0 V CR2025 lithium manganese built-in                        |

#### **ROADINGER Flightcase 4x AKKU TL-3 TCL Trusslight**

|                          |                                                     |
|--------------------------|-----------------------------------------------------|
| Maximum load:            | 25 kg                                               |
| Aluminum profile frames: | 25 mm                                               |
| Case handle:             | 1 pc/pcs                                            |
| Stop hinge:              | 2 pc/pcs                                            |
| Lock:                    | Butterfly lock: 1 pc/pcs                            |
| Use of brands:           | Branded hardware                                    |
| Material:                | Birch multiplex, 7 mm                               |
| Color:                   | Dark brown, laminated                               |
| Device compartment:      | 12 cm x 11.5 cm x 6.5 cm                            |
| Inside dimensions:       | 19 cm x 8 cm                                        |
| Dimensions:              | Width: 47.5 cm<br>Depth: 24.5 cm<br>Height: 21.5 cm |
| Weight:                  | 4.50 kg                                             |

#### **Scope of delivery:**

1 x device  
1 x remote control