

EUROLITE Set PAR-30 Spot sil + PAR-30 230V SMD 11W E-27 LED 3000K Art. No.: 20000285

PAR-30 housing with E-27 socket including PAR-30 lamp with LED technology

GTIN: 4026397598803



Features:

- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
 - Strong clamps with extension springs for safe hold and for quick opening of the rear housing cover
 - Blackened tube for precise light output
 - Suitable for different spot angles
 - Small lighting-systems can also be realized with a small budget
 - Control via plug and play
 - With mounting bracket
 - For PAR 30
 - For application areas such as: Clubs/dancing school; decoration; Trade fair and shop fitting; party room; restaurants, bars and hotels; advertisement/Shop window
 - Silent operation
 - <p>OMNILUX PAR-30 230V SMD 11W E-27 LED 3000K
- PAR-30 LED lamp**
- Easy lamp replacement
 - Energy-saving
 - Easy installation
 - Good color rendering index (CRI)

Logistic

EAN / GTIN: 4026397598803

Weight: 0,80 kg

Length: 0.30 m

Width: 0.22 m

Heigh: 0.21 m

Technical specifications:

Weight: 0.70 kg

EUROLITE PAR-30 Spot silver

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 100 W
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable length:	Approx. 0.4 m
Base:	E27
Lamp type:	Selectable
Color generation:	Via color filter frame
Control:	Plug and play
Construction:	PAR-30
Housing color:	Silver
Attachment system:	Mounting bracket
Material:	Aluminum
Slot for spot length:	12.8 cm x 12.8 cm
Dimensions:	Length: 23.5 cm Width: 14.5 cm Height: 21 cm
Weight:	0.47 kg
Noise classification:	Class 0 (no noise at all)
Material:	Aluminum
Material:	Aluminum
Dimensions:	Length: 12.6 cm Width: 12.6 cm Diameter: Ø 9.4 cm
Weight:	0.018 kg

OMNILUX PAR-30 230V SMD 11W E-27 LED 3000K

Voltage (lamps):	230 V, AC
Nominal wattage:	11 W
Base:	E27
Lamp type:	LED lamp; reflector lamp
Beam angle:	50°
Setup:	Easy installation
Color of light:	White
Color temperature:	3000K
Color rendering index (CRI):	82 Ra
Lead time:	0.2 s
Construction:	PAR-30
Burning position:	S180 (universal)
Lamp life:	20000 h
Luminous flux:	850 lm

Wavelength:	605 nm
Lamp current:	0.086 A
Dimensions (LxD):	92x95 mm
Weight:	0.19 kg
Energy efficiency class (A - G):	F
EPREL-Nr:	979334

Scope of delivery:

- 1 x spotlight
- 1 x filter frame
- 1 x user manual