



Features:

Logistic

EUROLITE PAR-16 Spot MR-16 black

PAR-16 housing with GX-5.3 socket for 12 V MR-16 lamp

- Mini spots for 50 mm cool beam lamps
- Detailed original reconstruction of the big stage spots
- Ideal for decoration purposes
- Control via plug and play
- With mounting bracket
- Available in various colors
- For PAR 16

OMNILUX MR-16 12V GX-5,3 5W LED COB 6400K

Cool-beam mirrored lamp

- Different illumination angles for different application areas
- Low power consumption
- Powerful LED illuminant with COB (Chip on Board) technology
- A homogenous light blend is thereby guaranteed
- Comfortable and fresh, white light
- Hot restrike
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	0.26 kg
---------	---------

EUROLITE PAR-16 Spot MR-16 black

Power supply:	12V AC
Power consumption:	Max. 50 W
Protection class:	Protection class III
Suitable lamp:	PAR-16 GX5.3
Power connection:	Fixed supply cord with open wires
Cable construction:	Miscellaneous Cables
Cable length:	Approx. 0.25 m
Base:	GX5.3
Lamp type:	Selectable
Color generation:	Via color filter frame
Control:	Plug and play
Housing color:	Black matte
Attachment system:	Mounting bracket
Material:	Aluminum, 1 mm
Slot for spot length:	8 cm x 8 cm
Dimensions:	Length: 17 cm Width: 11 cm Height: 13 cm
Weight:	0.22 kg
Diameter mounting holes:	2 x Ø10mm
Material:	Aluminum, 3 mm
Material:	Metal
Dimensions:	Length: 7.8 cm Width: 7.8 cm Diameter: Ø 5.3 cm
Weight:	0.026 kg

OMNILUX MR-16 12V GX-5,3 5W LED COB 6400K

Voltage (lamps):	12 V, AC
Nominal wattage:	5 W
Base:	GX5.3
Lamp type:	LED lamp
Lamp specification:	Hot restrike
Beam angle:	36°
Color of light:	White

Color temperature:	6400K
Lead time:	1 s
Construction:	MR-16; reflector; bi pin
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	30000 h
Luminous flux:	380 lm
Lamp current:	0.43 A
Dimensions (LxD):	65x51 mm
Weight:	0.04 kg

Scope of delivery:

- 1 x spotlight
- 1 x filter frame
- 1 x user manual