



### Features:

### Logistic

#### EUROLITE PAR-16 Spot MR-16 white

PAR-16 housing with GX-5.3 socket for 12 V MR-16 lamp

- Mini spots for 50 mm cool beam lamps
- Detailed original reconstruction of the big stage spots
- Ideal for decoration purposes
- Control via plug and play
- For PAR 16
- For application areas such as: Clubs/dancing school; decoration; Trade fair and shop fitting; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation

#### OMNILUX MR-16 12V GX-5,3 5W LED COB 6400K

Cool-beam mirrored lamp

- Different illumination angles for different application areas
- Low power consumption
- Powerful LED illuminant with COB (Chip on Board) technology
- A homogenous light blend is thereby guaranteed
- Comfortable and fresh, white light
- Hot restrike
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

|         |         |
|---------|---------|
| Weight: | 0.25 kg |
|---------|---------|

EUROLITE PAR-16 Spot MR-16 white

|                          |                                                       |
|--------------------------|-------------------------------------------------------|
| Power supply:            | 12V AC                                                |
| Power consumption:       | Max. 50 W                                             |
| Protection class:        | Protection class III                                  |
| Power connection:        | Fixed supply cord with open wires                     |
| Cable length:            | Approx. 0.25 m                                        |
| Base:                    | GX5.3                                                 |
| Lamp type:               | Selectable                                            |
| Color generation:        | Via color filter frame                                |
| Control:                 | Plug and play                                         |
| Housing color:           | White                                                 |
| Material:                | Aluminum                                              |
| Slot for spot length:    | 8 cm x 8 cm                                           |
| Dimensions:              | Length: 17 cm<br>Width: 11 cm<br>Height: 13 cm        |
| Weight:                  | 0.21 kg                                               |
| Noise classification:    | Class 0 (no noise at all)                             |
| Diameter mounting holes: | 2 x Ø10mm                                             |
| Material:                | Aluminum, 3 mm                                        |
| Material:                | Aluminum                                              |
| Dimensions:              | Length: 7.8 cm<br>Width: 7.8 cm<br>Diameter: Ø 5.3 cm |
| Weight:                  | 0.01 kg                                               |

OMNILUX MR-16 12V GX-5,3 5W LED COB 6400K

|                     |              |
|---------------------|--------------|
| Voltage (lamps):    | 12 V, AC     |
| Nominal wattage:    | 5 W          |
| Base:               | GX5.3        |
| Lamp type:          | LED lamp     |
| Lamp specification: | Hot restrike |
| Beam angle:         | 36°          |
| Color of light:     | White        |
| Color temperature:  | 6400K        |
| Lead time:          | 1 s          |

|                             |                          |
|-----------------------------|--------------------------|
| Construction:               | MR-16; reflector; bi pin |
| Operating temperature max.: | 40° C                    |
| Operating temperature min.: | 20° C                    |
| Burning position:           | S180 (universal)         |
| Lamp life:                  | 30000 h                  |
| Luminous flux:              | 380 lm                   |
| Lamp current:               | 0.43 A                   |
| Dimensions (LxD):           | 65x51 mm                 |
| Weight:                     | 0.04 kg                  |

**Scope of delivery:**

- 1 x spotlight
- 1 x filter frame
- 1 x user manual