

EUROLITE Set PAR-20 Spot sil + PAR-20 230V SMD 6W E-27 LED 6500K

PAR-20 housing with E-27 socket including PAR-20 lamp

Art. No.: 20000302

GTIN: 4026397601145



Features:

- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
 - Strong clamps with extension springs for safe hold and for quick opening of the rear housing cover
 - Blackened tube for precise light output
 - Strong cable tension relief
 - Control via plug and play
 - With mounting bracket
 - Available in various colors
 - For PAR 20
 - For application areas such as: Clubs/dancing school; decoration; Trade fair and shop fitting; party room; restaurants, bars and hotels; advertisement/Shop window
 - <p>OMNILUX PAR-20 230V SMD 6W E-27 LED 6500K
- PAR-20 lamp**
- Stronger with the same power consumption
 - Better brightness and color of light thanks to SMD LED
 - Good color rendering index (CRI)

Logistic

EAN / GTIN: 4026397601145

Weight: 0,60 kg

Length: 0.30 m

Width: 0.22 m

Heigh: 0.21 m

Technical specifications:

Weight: 0.40 kg

Energy efficiency class (A - G):

F

EUROLITE PAR-20 Spot silver

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 75 W
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable length:	Approx. 0.4 m
Base:	E27
Lamp type:	Selectable
Color generation:	Via color filter frame
Control:	Plug and play
Construction:	PAR-20
Housing color:	Silver
Attachment system:	Mounting bracket
Material:	Aluminum
Slot for spot length:	8.5 cm x 8.5 cm
Dimensions:	Width: 15 cm Depth: 18 cm Height: 11.2 cm Diameter: Ø 8 cm
Weight:	0.32 kg
Diameter mounting holes:	2 x Ø10mm
Material:	Aluminum, 3 mm
Material:	Aluminum
Dimensions:	Length: 8.4 cm Width: 8.4 cm Diameter: Ø 6.1 cm

OMNILUX PAR-20 230V SMD 6W E-27 LED 6500K

Operating voltage:	230
Nominal wattage:	6 W
Base:	E27
Lamp type:	LED lamp; reflector lamp
Beam angle:	50°
Color of light:	White
Color temperature:	6500K
Color rendering index (CRI):	81 Ra
Lead time:	0.2 s
Construction:	PAR-20
Burning position:	S180 (universal)
Lamp life:	20000 h
Luminous flux:	510 lm
Wavelength:	454 nm

Lamp current:	0.053 A
Dimensions (LxD):	86x64 mm
Weight:	0.10 kg
Photobiological safety:	Risk Group 0
Energy efficiency class (A - G):	F
EPREL-Nr:	1015317

Scope of delivery:

- 1 x spotlight
- 1 x filter frame
- 1 x user manual