

EUROLITE Set 4x LED SLS-603 + Case EC-SL4M size M

4x flat spotlight with 5 x 3 W 3in1 LED including practical flightcase

Art. No.: 20000306

GTIN: 4026397601183



List price: 522.41 €

incl. 19% VAT.

Features:

- Slim design for space-saving applications
 - DMX and power terminals intelligently designed for easy wiring
 - 6 LEDs 3 W high-power 4in1 RGB/UV (homogenous color mix)
 - Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
 - UV effect; strobe effect
 - Integrated show programs
 - Can be operated in 4; 8 CH mode
 - The device is cooled by cooling fan
 - Control via stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function
 - With a beam angle of 11°
 - With double bracket
 - 4 digit 7-segment LED display
 - Mains input and output for power linking up to 8 units
 - Application possibility: Standing; suspended; on stand
 - For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels
 - <p>ROADINGER Flightcase EC-SL4M 4x SLS size M
- Trunk case**
- With 4 device compartments
 - High-quality workmanship with plywood multi-layer glued 7 mm, dark brown, laminated
 - Interior with felt cover
 - Aluminum profile frames 30mm with rounded edges
 - Hinged, chromium plated case handle
 - 2 chrome tip-over locks
 - 1 high-quality butterfly lock

Logistic

EAN / GTIN: 4026397601183

Weight: 15,78 kg

Length: 0.82 m

Width: 0.41 m

Height: 0.52 m

- Closes with a
- Rubber feet
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	14.04 kg
---------	----------

EUROLITE LED SLS-603 TCL + UV Floor

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	20 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	6 x 3 W high-power 4in1 RGB/UV (homogenous color mix)
DMX channels:	4; 8
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	1 x cooling fan
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function
Fixtures available for:	Light´ J; LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; Colorchief
Beam angle:	11°
Beam angle (1/2 peak):	11°
Beam angle (1/10 peak):	28°
Housing color:	Black
Attachment system:	Double bracket
Display type:	4 digit 7-segment LED display
Material:	Plastic; metal; ABS Acrylonitrile butadiene styrene
Dimensions:	Width: 23 cm Depth: 11 cm Height: 23 cm
Weight:	1.41 kg
Noise classification:	Class 2 (slight noise)
Photobiological safety:	Risk Group 0
Cable construction:	3 x 0.75 mm² H05VV-F
Cable length:	Approx. 1.1 m
Diameter mounting holes:	5 x Ø11mm
Material:	Metal, 2 mm
Color:	Black

Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
----------	---

ROADINGER Flightcase EC-SL4M 4x SLS size M

Maximum load:	25 kg
Aluminum profile frames:	30 mm
Case handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Transport aid:	Rubber feet
Material:	Plywood multi-layer glued, 7 mm
Color:	Dark brown, laminated; black, laminated
Compartment dimensions:	11.5 cm x 24.5 cm x 34 cm
Inside dimensions:	49 cm x 25 cm x 39 cm
Dimensions:	Width: 52.5 cm Depth: 28.5 cm Height: 44.5 cm
Weight:	8.40 kg

Scope of delivery:

- 1 x spotlight
- 1 x power cord
- 1 x remote control
- 1 x battery
- 1 x user manual