

EUROLITE Set 4x LED PAR-56 QCL Short sil + PRO Case

4x PAR-56 Spot with 9 x 8 W 4in1 LED and RGBW color mixing including PRO flightcase

Art. No.: 20000320

GTIN:



Features:

- Operable in stand-alone mode or via DMX
- Adjustable microphone sensitivity via control board
- Functions: Static colors, RGBW color mixture, auto mode, internal programs, dimmer and strobe settings via DMX, Master/Slave
- Equipped with 9 x 8 W 4in1 LED in red, green, blue and white
- Locking possibility at the mounting bracket
- Comfortable addressing and setting via control board with LED display and four operating buttons
- Additional controlling possibility via the EUROLITE IR-7 remote control, included in delivery
- Switch-mode power supply for operation between 100 and 240 volts
- Ready for connection via included IEC power cord with safety power plug
- Silver or black housing available
- 9 LEDs 8 W high-power 4in1 RGBW (homogenous color mix)
- Strobe effect
- Can be operated in 4; 8; 6 CH mode
- Control via stand-alone; DMX; IR remote control; sound to light via microphone
- Flicker-free
- With a beam angle of 8°
- <p>ROADINGER Flightcase 4x PAR-56 Spot short

Trunk case

- Detachable compartments - case can also be used as universal transport case
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- Hinged, chromium plated case handle

Logistic

- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Closes with a
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	14.66 kg
---------	----------

EUROLITE LED PAR-56 QCL Short sil

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	9 x 8 W high-power 4in1 RGBW (homogenous color mix)
DMX channels:	4; 8; 6
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone
Fixtures available for:	Light´ J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Projection:	Flicker-free
Beam angle:	8°
Beam angle (1/2 peak):	8°
Beam angle (1/10 peak):	25°
Housing color:	Silver
Dimensions:	Width: 20.5 cm Depth: 17.5 cm Height: 23 cm
Weight:	1.76 kg
Photobiological safety:	Risk Group 0
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in

ROADINGER Flightcase 4x PAR-56 Spot short

Maximum load:	25 kg
Aluminum profile frames:	30 mm

Case handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Compartment dimensions:	21.5 cm x 21.5 cm x 23 cm
Inside dimensions:	43 cm x 43 cm x 23 cm
Dimensions:	Width: 48.5 cm
	Depth: 48.5 cm
	Height: 31 cm
Weight:	7.60 kg

Scope of delivery:

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 1 x remote control
- 1 x battery