

EUROLITE Set 2x PLB-230 + Case

2x High-Power Beam with OSRAM SIRIUS HRI 230 W lamp including PRO flightcase

Art. No.: 20000330

GTIN:



Features:

- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- Effect wheel with rotating 3-facet prism and 8-facet prism and frost filter
- Strobe effect with adjustable speed
- Random strobe effect
- Electronic dimmer (0-100%)
- Exact positioning via 16 bit PAN/TILT movement resolution
- Automatic position correction
- PAN angle switchable between 540° and 630°
- Number of scenes in Program Run can be changed individually
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Software upload by optional accessories via DMX link
- With already installed Osram Sirius HRI 230 W lamp
- 12 LEDs 3 W 3in1 RGB
- PAN angle switchable between 540° and 630°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Gobo wheel with rotating gobos; focus motor-driven
- Gobo effect
- Color wheel with 14 dichroic filters plus open
rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 8 gobos and open
shake effect
- Gobos changeable
- Slot-in gobo system for easy gobo replacement
- Can be operated in 17; 19; 21; 24 CH mode
- The device is cooled by temperature-controlled fan

Logistic

- Control via RDM; DMX; stand-alone; W-DMX by wireless solution; sound to light via microphone
 - With a beam angle of 1.3°
 - <p>ROADINGER Flightcase 2x DMH-90/150/DMB-60/PLB-230
- Trunk case with castors, PRO version**
- For optimal security
 - With 2 device compartments
 - High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
 - Interior with foam padding
 - Aluminum profile frames 30mm with rounded edges
 - 4 hinged, chromium plated case handles
 - 2 high-quality butterfly locks
 - Closes with a
 - 4 x castors with 2 locking brakes
 - Branded hardware
 - Made in Europe
 - For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

FUTURELIGHT PLB-230 Moving Head

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	325.00 W
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug
Lamp type:	Discharge lamp
LED type:	12 x 3 W 3in1 RGB
Max. TILT movement:	270° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540°, 630° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	0 - 20 Hz
Equipment:	Gobo wheel with rotating gobos; focus motor-driven
Color generation:	Color wheel with 14 dichroic filters plus open Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with rotating gobos, 8 gobos and open Outside diameter 14mm Image diameter 6mm Shake effect Gobos changeable Slot-in gobo system for easy gobo replacement
DMX channels:	17; 19; 21; 24
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	RDM; DMX; stand-alone; W-DMX by wireless solution; sound to light via microphone
Fixtures available for:	LED PC-Control 512; Light Captain; Light J
Carrier frequency:	2.4 GHz

Beam angle:	1.3°
Beam angle (1/2 peak):	1.3°
Housing color:	Black
Dimensions:	Width: 25 cm Depth: 42.4 cm Height: 34.3 cm
Weight:	16.20 kg
Noise classification:	Class 3 (clearly perceptible sounds)

ROADINGER Flightcase 2x DMH-90/150/DMB-60/PLB-230

Maximum load:	100 kg
Aluminum profile frames:	30 mm
Case handle:	4 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	38.5 cm x 22 cm x 38 cm
Inside dimensions:	56 cm x 43 cm x 46.5 cm
Middle compartment:	12 cm x 43 cm x 46.5 cm
Dimensions:	Width: 96 cm Depth: 47 cm Height: 72 cm
Weight:	25.90 kg

Scope of delivery: