



**The article is no longer in our assortment.**

### Features:

### Logistic

#### EUROLITE LED TMH-X20 Moving Head Spot

Bright spot with 200 W LED, zoom, gobo wheels, color wheel, 2 prisms

- Equipped with a white 200 W COB LED
- Switchable color change (mode 1: only full colors, mode 2: color-change at every position)
- Rainbow effect with adjustable speed in both directions
- Effect wheel with rotating 6 fold linear prism and 3-facet prism
- The prism rotate in both directions and at different speeds
- Exact positioning via 16 bit PAN/TILT movement resolution
- Positioning within 540° PAN and 270° TILT
- Strobe effect with 1-18 flashes per second
- Strobe effect with adjustable speed
- Random strobe effect
- Motorized zoom (12°-23°)
- Motorized focus
- Iris
- Dimmer
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Sound control; microphone sensitivity adjustable via control board
- Internal programs
- Automatic position correction

- Control board with touch LCD and foil-keyboard for adjusting the DMX-starting address, PAN/TILT Reverse, Program, Reset
- P-Con terminals for power linking up to 8 units
- Switch-mode power supply for operation between 100 and 240 volts
- 1 LED 200 W high-power cold white (CW)
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Gobo wheel with rotating gobos; gobo wheel with static gobos; prism linear; prism 3-fold; focus motor-driven; iris; zoom motor driven
- Gobo effect; beam effect
- Color wheel with 7 dichroic filters plus open
- Gobo wheel with static gobos, 9 gobos and open
- Gobo wheel with rotating gobos, 7 gobos and open<BR>gobos changeable
- Shake effect
- Slot-in gobo system for easy gobo replacement
- Can be operated in 18 CH mode
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone
- Flicker-free
- With a beam angle of 12° - 23°

### ROADINGER Flightcase 2x TMH-X20

Flightcase for two TMH-X20

- Interior suitable for two TMH-X20 Moving-Heads
- With additional storage compartment
- Interior and cover (not removable) upholstered with foam
- High-quality workmanship with multiplex birch wood, dark brown laminated
- Aluminum profile frames (30 mm) with rounded edges
- Three-leg, medium-sized steel ball corners (chrome)
- 4 stacking dishes for stacking the cases
- 2 x hinge
- 2 high-quality butterfly locks
- 2 case handles
- Castors
- For further information about this product, please refer to the Data Sheet under "Downloads"

### Technical specifications:

#### EUROLITE LED TMH-X20 Moving Head Spot

|                     |                                                                                                                                             |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:       | 100-240 V AC, 50/60 Hz                                                                                                                      |
| Power consumption:  | 260 W                                                                                                                                       |
| Power connection:   | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug (provided)                                             |
| Power output:       | 1 x P-Con (grey), mounting version                                                                                                          |
| Lamp type:          | LED lamp                                                                                                                                    |
| LED type:           | 1 x 200 W high-power cold white (CW)                                                                                                        |
| Max. TILT movement: | 270° exact positioning (16 bit resolution) auto<br>position correction (feedback)                                                           |
| Max. PAN movement:  | 540° exact positioning (16 bit resolution) auto<br>position correction (feedback)                                                           |
| Flash rate:         | 0 - 18 Hz                                                                                                                                   |
| Equipment:          | Gobo wheel with rotating gobos; gobo wheel with<br>static gobos; prism linear; prism 3-fold; focus<br>motor-driven; iris; zoom motor driven |
| Color generation:   | Color wheel with 7 dichroic filters plus open                                                                                               |
| Gobos:              | Gobo wheel with static gobos, 9 gobos and open                                                                                              |

|                         |                                                   |
|-------------------------|---------------------------------------------------|
|                         | Gobo wheel with rotating gobos, 7 gobos and open  |
|                         | Outside diameter 25mm                             |
|                         | Image diameter 23mm                               |
|                         | Gobos changeable                                  |
|                         | Shake effect                                      |
|                         | Slot-in gobo system for easy gobo replacement     |
| DMX channels:           | 18                                                |
| DMX input:              | 3-pin XLR (M) mounting version                    |
| DMX output:             | 3-pin XLR (F) mounting version                    |
| Cooling:                | Cooling fan                                       |
| Control:                | Stand-alone; DMX; sound to light via microphone   |
| Fixtures available for: | LED PC-Control 512; Light Captain                 |
| Projection:             | Flicker-free                                      |
| Beam angle:             | 12° - 23°                                         |
| Beam angle (1/2 peak):  | 12 - 23°                                          |
| Beam angle (1/10 peak): | 12 - 23°                                          |
| Housing color:          | Black                                             |
| Dimensions:             | Width: 42.5 cm<br>Depth: 33 cm<br>Height: 48.5 cm |
| Weight:                 | 17.95 kg                                          |

#### ROADINGER Flightcase 2x TMH-X20

|                         |                                                   |
|-------------------------|---------------------------------------------------|
| Maximum load:           | 50 kg                                             |
| Transport aid:          | Castors                                           |
| Material:               | Birch multiplex, 7 mm                             |
| Color:                  | Dark brown, laminated                             |
| Compartment dimensions: | 31 cm x 42.5 cm x 53 cm                           |
| Accessory compartment:  | 7 cm x 42.5 cm x 53 cm                            |
| Inside dimensions:      | 59 cm x 42.5 cm x 53 cm                           |
| Dimensions:             | Width: 79 cm<br>Depth: 48.5 cm<br>Height: 76.5 cm |
| Weight:                 | 25.40 kg                                          |

#### Scope of delivery:

2 x omega bracket