

## EUROLITE Set 4x LED SLS-9 Hybrid HCL + Soft Bag

4x flat spotlight with strobe and UV effects, including IR remote control and soft bag

Art. No.: 20000352

GTIN:



### Features:

- Powerful hybrid effect - spot, strobe and UV effect in one device
- Flat version requires minimal space when mounting
- 24 LEDs SMD 5050 cold white (CW) (homogenous color mix)
- 1 LED 15 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)
- 9 LEDs 10 W high-power 6in1 RGBWA/UV (homogenous color mix)
- Color macros adjustable; colors preset; program selection; color blend stepless; Dimmer electronic
- Strobe effect; UV effect
- Can be operated in 2; 6; 14; 26 CH mode
- Control via stand-alone; DMX; sound to light via microphone; master/slave function
- Flicker-free
- With a beam angle of 16°
- With double bracket
- Mains input and output for power linking up to 8 units
- <p>EUROLITE SB-18 Soft Bag
- **Practical soft bag for 4 PRO Pixel Slim PAR-12/ SLS-400**
- Made of easy-care nylon
- With Outside pocket
- With dividers
- With 5 device compartments
- High-quality workmanship with textile , black
- Interior with foam padding
- 2 carrying straps

### Logistic

## Technical specifications:

|         |         |
|---------|---------|
| Weight: | 9.00 kg |
|---------|---------|

### EUROLITE LED SLS-9 Hybrid HCL

|                         |                                                                                                                                                                                   |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz                                                                                                                                                            |
| Power consumption:      | 70 W                                                                                                                                                                              |
| Power connection:       | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)                                                                                  |
| Power output:           | 1 x IEC connector (F) mounting version                                                                                                                                            |
| Lamp type:              | LED lamp                                                                                                                                                                          |
| LED type:               | 24 x SMD 5050 cold white (CW) (homogenous color mix)<br>1 x 15 W COB (chip-on-board) 4in1 RGBW (homogenous color mix)<br>9 x 10 W high-power 6in1 RGBWA/UV (homogenous color mix) |
| Flash rate:             | 0 - 20 Hz                                                                                                                                                                         |
| DMX channels:           | 2; 6; 14; 26                                                                                                                                                                      |
| DMX input:              | 1 x 3-pin XLR (M) mounting version                                                                                                                                                |
| DMX output:             | 1 x 3-pin XLR (F) mounting version                                                                                                                                                |
| Control:                | Stand-alone; DMX; sound to light via microphone; master/slave function                                                                                                            |
| Fixtures available for: | LED PC-Control 512; Light Captain; Light J                                                                                                                                        |
| Projection:             | Flicker-free                                                                                                                                                                      |
| Beam angle:             | 16°                                                                                                                                                                               |
| Beam angle (1/2 peak):  | 16°<br>28°                                                                                                                                                                        |
| Beam angle (1/10 peak): | 39°<br>54°                                                                                                                                                                        |
| Housing color:          | Black                                                                                                                                                                             |
| Attachment system:      | Double bracket                                                                                                                                                                    |
| Dimensions:             | Width: 28 cm<br>Depth: 12.2 cm<br>Height: 28.6 cm                                                                                                                                 |
| Weight:                 | 2.10 kg                                                                                                                                                                           |
| Photobiological safety: | Risk Group 0                                                                                                                                                                      |
| Battery:                | 1 x button cell 3.0 V CR2025 lithium manganese built-in                                                                                                                           |

### EUROLITE SB-18 Soft Bag

|               |       |
|---------------|-------|
| Maximum load: | 25 kg |
|---------------|-------|

|                 |                                               |
|-----------------|-----------------------------------------------|
| Carrying strap: | 2 pc/pcs                                      |
| Material:       | Textile                                       |
| Color:          | Black                                         |
| Dimensions:     | Width: 47 cm<br>Depth: 24 cm<br>Height: 30 cm |
| Weight:         | 0.60 kg                                       |

**Scope of delivery:**

1 x remote control