



The article is no longer in our assortment.

Features:

Logistic

EUROLITE LED MFX-3 Action Cube

Moving Effect with 6 light beams and Mood Light strips on the edges

- Beam effect with 6 lenses and 10 W quadcolor LEDs in RGBW colors and 12 LED mood light strips with 4 RGB SMD LEDs each
- Compact lightweight
- With infinity function for unlimited TILT movement
- Positioning within 630° PAN and 200° TILT
- PAN-angle switchable between 630° and 540°
- Functions: Colored beams, LED mood light strips, auto mode, color presets, color change, Master/Slave function, built-in programs, stepless RGBW color mixture
- Masterdimmer
- Strobe effect with 1-25 flashes per second and with adjustable speed
- Random strobe effect
- Automatic position correction
- Exact positioning via 16 bit PAN/TILT movement resolution
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Addressing via control panel with 4-digit LED display
- Switch-mode power supply for operation between 100 and 240 volts
- Ready for connection with power cord and safety plug
- 48 LEDs 0.2 W SMD 2835 3in1 RGB (homogenous color mix)
- 6 LEDs 10 W SMD 5050 4in1 RGBW (homogenous color mix)

- PAN angle switchable between 540° and 630°
- Auto position correction (feedback)
- Multi beam effect
- Can be operated in 14; 16 CH mode
- Control via DMX; stand-alone; sound to light via microphone
- Flicker-free
- With a beam angle of 9°

ROADINGER Flightcase 2x LED MFX-3

PRO flightcase for 2 x LED MFX-3

- Fitted for two devices
- Additional accessory compartment
- Compartments upholstered with foam
- High-quality workmanship with birch multiplex, dark brown laminated
- Aluminum profile frames with rounded edges
- Three-leg steel ball corners
- 2 hinges
- 2 chrome butterfly locks
- 2 chrome case handles
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	20.25 kg
---------	----------

EUROLITE LED MFX-3 Action Cube

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	75 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	48 x 0.2 W SMD 2835 3in1 RGB (homogenous color mix) 6 x 10 W SMD 5050 4in1 RGBW (homogenous color mix)
Max. TILT movement:	200° positioning plus infinity auto position correction (feedback)
Max. PAN movement:	540°, 630° positioning auto position correction (feedback)
Flash rate:	0 - 25 Hz
DMX channels:	14; 16
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; stand-alone; sound to light via microphone
Fixtures available for:	Light J; LED PC-Control 512; Light Captain
Projection:	Flicker-free

Beam angle:	9°
Beam angle (1/2 peak):	9°
Housing color:	Black
Dimensions:	Width: 25 cm Depth: 18 cm Height: 35 cm
Weight:	5.35 kg

ROADINGER Flightcase 2x LED MFX-3

Maximum load:	25 kg
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Accessory compartment:	10.5 cm x 26.5 cm x 34 cm
Compartment dimensions:	21.5 cm x 26.5 cm x 34 cm
Dimensions:	Width: 60 cm Depth: 31 cm Height: 43 cm
Weight:	9.55 kg

Scope of delivery:
1 x omega bracket