

EUROLITE Set 4x LED THA-100F MK2 Theater-Spot + Case

4x Fresnel spot, 100 W warm white LED, CRI >90, quiet, DMX including PRO flightcase

Art. No.: 20000363

GTIN:



Features:

- Color temperature 3200 K
- Electronic dimmer (0-100%)
- Various dimmer curves selectable
- With color filter frame
- Mains input and output for power linking up to 8 units
- 1 LED 100 W COB (chip-on-board) warm white (WW)
- Zoom manual
- Strobe effect
- Can be operated in 1; 3 CH mode
- The device is cooled by low-noise cooling fan
- Control via stand-alone; DMX
- With a beam angle of 6° - 46°
- Very high color rendering index (CRI)
- With mounting bracket
- LCD display
- <p>ROADINGER Flightcase 4x LED THA-100F/THA-120PC with wheels
- **Trunk case with castors, PRO version**
- With accessory compartment
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Closes with a

Logistic

- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	55.80 kg
---------	----------

EUROLITE LED THA-100F MK2 Theater-Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	120 W
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (grey), mounting version
Lamp type:	LED lamp
LED type:	1 x 100 W COB (chip-on-board) warm white (WW)
Equipment:	Zoom manual
DMX channels:	1; 3
DMX input:	3-pin XLR (M) mounting version 5-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version 5-pin XLR (F) mounting version
Cooling:	Low-noise cooling fan
Control:	Stand-alone; DMX
Fixtures available for:	LED PC-Control 512; Light Captain; Light´J
Beam angle:	6° - 46°
Beam angle (1/2 peak):	6 - 31°
Beam angle (1/10 peak):	22 - 46°
Color temperature:	3200K
Color rendering index (CRI):	94 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Dimensions:	Length: 37 cm Width: 33.5 cm Height: 26.5 cm
Weight:	6.30 kg
Noise classification:	Class 2 (slight noise)

ROADINGER Flightcase 4x LED THA-100F/THA-120PC with wheels

Aluminum profile frames:	25 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Middle compartment:	10.5 cm x 59 cm x 40.5 cm
Outer compartment:	33 cm x 29.5 cm x 40.5 cm
Inside dimensions:	76.5 cm x 59 cm x 40.5 cm
Dimensions:	Width: 82 cm Depth: 65.5 cm Height: 67.5 cm
Weight:	27.60 kg

Scope of delivery:

1 x filter frame
1 x spotlight
1 x user manual
1 x power cord