

EUROLITE Set 4x AKKU TL-3 QuickDMX + Soft Bag

4x Spot for lighting within trussing, 3 x 3 W 3in1 LED, QuickDMX transceiver including soft bag

Art. No.: 20000398

GTIN: 4026397620191



Features:

- Compact and bright
- Ideal for ALUTRUSS DECOLOCK DQ3 3-point system
- Integrated QuickDMX transceiver for wireless DMX control
- Threaded inserts for suspended installation
- Cordless, flexible and versatile
- Battery operation up to 16h depending on program used
- 3 LEDs 3 W SMD 8072 3in1 RGB (homogenous color mix)
- Dimmer electronic; color blend stepless; color change adjustable; Dimmer speed (step response) adjustable
- Strobe effect
- Can be operated in 3; 5; 8 CH mode
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; QuickDMX; IR remote control; sound to light via microphone
- Flicker-free
- With a beam angle of 11°
- LCD display
- 3 x rubber feet
- Mains input and output for power linking up to 8 units
- For application areas such as: Stage; clubs/dancing school; decoration; wedding/gala/events; mobile djs / entertainer; rental; advertisement/Shop window
- Silent operation
- Application possibility: Standing; suspended
- <p>EUROLITE SB-4 Soft Bag L
- Black soft bag for up to 4 devices, 320 x 320 x 200 mm**
- Practical transport bag offers enough space for several lighting effects and accessories
- With dividers

Logistic

EAN / GTIN: 4026397620191

Weight: 7,00 kg

Length: 0.82 m

Width: 0.41 m

Height: 0.35 m

- With 2 Outside pockets
- With 4 device compartments
- High-quality workmanship with nylon , black, water repellent
- Interior with foam padding
cover with foam padding
- 2 carrying straps

Technical specifications:

Weight:	5.60 kg
---------	---------

EUROLITE AKKU TL-3 TCL Trusslight QuickDMX

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	25 W
Protection class:	Protection class I
Power connection:	Battery/battery pack Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Cable length:	Approx. 1.2 m
Power output:	1 x IEC connector (F) mounting version
Fuse:	5 x 20 mm, F 5 A
Battery pack type:	1 x lithium ion 11.1 V, 4400 mAh, 48.84 Wh
Battery pack:	Battery operation up to 16h depending on program used Recharging time 3h
Lamp type:	LED lamp
LED type:	3 x 3 W SMD 8072 3in1 RGB (homogenous color mix)
Flash rate:	0 - 23 Hz
DMX channels:	3; 5; 8
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; QuickDMX; IR remote control; sound to light via microphone
Fixtures available for:	Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Carrier frequency:	2.4 GHz
Beam angle:	11°
Beam angle (1/2 peak):	11°
Beam angle (1/10 peak):	24°
Housing color:	Black

Attachment system:	M10 thread
Display type:	LCD display
Transport aid:	3 x rubber feet
Dimensions:	Width: 12.1 cm Depth: 10.8 cm Height: 14.5 cm
Weight:	1.27 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in

EUROLITE SB-4 Soft Bag L

Maximum load:	25 kg
Carrying strap:	2 pc/pcs
Material:	Nylon
Color:	Black, water repellent
Compartment dimensions:	15 cm x 15 cm x 20 cm
Inside dimensions:	32 cm x 32 cm x 20 cm
Dimensions:	Width: 32 cm Depth: 41 cm Height: 20 cm
Weight:	0.52 kg

Scope of delivery:

4 x EUROLITE AKKU TL-3 TCL Trusslight QuickDMX

1 x spotlight
 1 x user manual
 1 x power cord
 1 x remote control
 1 x battery
 1 x declaration of conformity

1 x EUROLITE SB-4 Soft Bag L

1 x bag